INDEX

RUBBER CHEMISTRY AND TECHNOLOGY

VOLUME 44, 1971

AUTHOR INDEX

ALLAN, G., see PRICE, C., (3) 744
ALTENAU, A. G., see CARLSON, D. W., (5) 1278
ANTHONY, J. G., see FOLAND, D. L., (3) 838

BARANWAL, K., Effect of SBR styrene content, cis-1,4-polybutadiene, and black-oil loadings on coefficient of friction (abstract), (5) 1443
BARNEY, A. L., G. H. KALB, AND A. A. KHAN, Vulcanizate properties from a new perfluoroelastomer, (3) 660
BARNHART, R. R. see BROWNING, G. R., (5) 1441
BHAKUNI, R. S., J. M. GINGO, AND A. G. CAUSA, Tire fiber rheology (Abstract), (3) 846
BLANCHARD, A. F., Intrinsic linkage reinforcement from swelling measurements of effective values of ϕ., (5) 1249
——, Crosslinking, filler, or transition constraint of polymer networks. I and II. (5) 1208; 1227
BOONSTRA, B. B., see LAMBERT, D. H., (1) 214
——, and F. A. HECKMAN, Studies on abrasion and traction using the scanning electron microscope (Abstract), (5) 1451
BRALEY, S. A., Elastomers for implantation in the human body (Review), (2) 363
BRENNER, F. C. AND A. KONDO, Research for a uniform quality grading system for tires. IV. Tread wear, (1) 106
——, ——, AND G. B. COHEN, Research for a uniform quality grading system for tires. V. Effect of environment on tread wear rate, (4) 952
——, see KONDO, A., (4) 969
BRETT, T. J., see MASTROMATTEO, R. P., (4) 1065
——, see KIENLE, R. N., (4) 996
BROATCH, W. N., Polyester as a reinforcement in tire belts (Abstract), (3) 850
BROWN, J. E., JR., Tire properties and vehichle cornering stability. I. Stabilization of oversteering vehichles by tire parameter variations (Abstract), (5) 1456
BROWNING, G. R., AND R. R. BARNHART, Leaching of antiozonants from a tire compound (Abstract), (5) 1441
BUCHANAN, R. A., H. C. KATZ, C. R. RUSSELL, AND C. E. RIST, Starch in rubber. Powdered elastomers from starch-encased latex particles (Abstract), (3) 842
BURGESS, K. A., C. E. SCOTT, AND W. M. HESS, Vulcanizate performance as a function of carbon black morphology, (1) 230
——, see SCOTT, C. E., (5) 1445
BUSSEMAKER, O. K. F., see MOSCOU, L., (3) 805

CALDERON, N., see SCOTT, K. W., (5) 1341
CALLAN, J. E., see HESS, W. M. (3) 814
CAMPBELL, D. S., Structural characteristization of vulcanizates. XI. Network-bound accelerator residues, (3) 771
CARLSON, D. W., A. C. RANSAW, AND A. G. ALTENAU, Determination of polymer composition of rubber vulcanizates, (5) 1278
CARMAN, C. J. AND C. E. WILKES, Monomer sequence distribution in ethylene propylene elastomers. I. Measurement by carbon-13 nuclear magnetic resonance spectroscopy, (3) 781
CASALE, A., R. S. PORTER, AND J. F. JOHNSON, The mechanochemistry of high polymers (Review), (2) 534
CASS, P. J., see ROSTLER, K. S., (5) 1448
CAUSA, A. G., see BHAKUNI, R. S., (3) 846
CAYWOOD, S. W., JR., Ethylene propylene vinylcyclohexene terpolymers, (3) 653
——, see LEIBU, H. I., (5) 1436

INDEX

RUBBER CHEMISTRY AND TECHNOLOGY

VOLUME 44, 1971

AUTHOR INDEX

ALLAN, G., see PRICE, C., (3) 744
ALTENAU, A. G., see CARLSON, D. W., (5) 1278
ANTHONY, J. G., see FOLAND, D. L., (3) 838

BARANWAL, K., Effect of SBR styrene content, cis-1,4-polybutadiene, and black-oil loadings on coefficient of friction (abstract), (5) 1443
BARNEY, A. L., G. H. KALB, AND A. A. KHAN, Vulcanizate properties from a new perfluoroelastomer, (3) 660
BARNHART, R. R. see BROWNING, G. R., (5) 1441
BHAKUNI, R. S., J. M. GINGO, AND A. G. CAUSA, Tire fiber rheology (Abstract), (3) 846
BLANCHARD, A. F., Intrinsic linkage reinforcement from swelling measurements of effective values of ϕ., (5) 1249
——, Crosslinking, filler, or transition constraint of polymer networks. I and II. (5) 1208; 1227
BOONSTRA, B. B., see LAMBERT, D. H., (1) 214
——, and F. A. HECKMAN, Studies on abrasion and traction using the scanning electron microscope (Abstract), (5) 1451
BRALEY, S. A., Elastomers for implantation in the human body (Review), (2) 363
BRENNER, F. C. AND A. KONDO, Research for a uniform quality grading system for tires. IV. Tread wear, (1) 106
——, ——, AND G. B. COHEN, Research for a uniform quality grading system for tires. V. Effect of environment on tread wear rate, (4) 952
——, see KONDO, A., (4) 969
BRETT, T. J., see MASTROMATTEO, R. P., (4) 1065
——, see KIENLE, R. N., (4) 996
BROATCH, W. N., Polyester as a reinforcement in tire belts (Abstract), (3) 850
BROWN, J. E., JR., Tire properties and vehichle cornering stability. I. Stabilization of oversteering vehichles by tire parameter variations (Abstract), (5) 1456
BROWNING, G. R., AND R. R. BARNHART, Leaching of antiozonants from a tire compound (Abstract), (5) 1441
BUCHANAN, R. A., H. C. KATZ, C. R. RUSSELL, AND C. E. RIST, Starch in rubber. Powdered elastomers from starch-encased latex particles (Abstract), (3) 842
BURGESS, K. A., C. E. SCOTT, AND W. M. HESS, Vulcanizate performance as a function of carbon black morphology, (1) 230
——, see SCOTT, C. E., (5) 1445
BUSSEMAKER, O. K. F., see MOSCOU, L., (3) 805

CALDERON, N., see SCOTT, K. W., (5) 1341
CALLAN, J. E., see HESS, W. M. (3) 814
CAMPBELL, D. S., Structural characteristization of vulcanizates. XI. Network-bound accelerator residues, (3) 771
CARLSON, D. W., A. C. RANSAW, AND A. G. ALTENAU, Determination of polymer composition of rubber vulcanizates, (5) 1278
CARMAN, C. J. AND C. E. WILKES, Monomer sequence distribution in ethylene propylene elastomers. I. Measurement by carbon-13 nuclear magnetic resonance spectroscopy, (3) 781
CASALE, A., R. S. PORTER, AND J. F. JOHNSON, The mechanochemistry of high polymers (Review), (2) 534
CASS, P. J., see ROSTLER, K. S., (5) 1448
CAUSA, A. G., see BHAKUNI, R. S., (3) 846
CAYWOOD, S. W., JR., Ethylene propylene vinylcyclohexene terpolymers, (3) 653
——, see LEIBU, H. I., (5) 1436

CHARRIER, J. M. AND A. N. GENT, Inflation and compression of rubber tubes between parallel plates, (5) 1380
CHASSET, R., see THIRION, P., (5) 1256
CHIRICO, V. E., see SCOTT, C. E., (5) 1445
CLAPSON, B. E. see LAKE, G. J., (5) 1186
COHEN, G. B., see BRENNER, F. C., (4) 952
COLEMAN, M. M., see KOENIG, J. L., (1) 71
——, see STARMER, P. H., (3) 854
——, see SHELTON, J. R., (4) 904
COLOMB, H. O., JR. AND D. J. TRECKER, Radiation-convertible polymers from norbornenyl derivatives, (3) 587
CONANT, F. S., Tire temperatures (Review), (2) 397
CORMAN, B. G., M. L. DEVINEY, AND L. E. WHITTINGTON, Migration of extender oil in natural and synthetic rubber VI. The use of oil type molecules as penetrants to elucidate elastomeric molecular structure (Abstract), (5) 1430
COOK, F. R., see VOET A., (1) 175
COZEWITH, C., see GARDNER, I. J., (4) 1015

D'AMICO, J. J. AND E. MORITA, Rubber chemicals from cyclic amines. V. Thiocarbamyl sulfenamide accelerators derived from 3-azabicyclo[3.2.2]nonane, (4) 889
——, ——, Rubber chemicals from cyclic amines. VI. 2-(4-morpholinodithio) benzothiazole and related compounds as curing agents, (4) 898
——, see MORITA, E., (4) 881
DAVIS, D. D., see KAUFMAN, S., (3) 843
DECANDIA, F., see PRICE, C., (3) 744
DEVINEY, M. L., JR., AND L. E. WHITTINGTON, The migration of extender oil in natural and synthetic rubber. V. Dependence of diffusion rates on oil concentration and elastomer blend ratios. The locus of oil in a simulated tire during service, (1) 87.
——, see WADE, W. H., (1) 218
——, see LEWIS, J. E., (3) 855
——, see CORMAN, B. G., (5) 1430
DEWHURST, H. A., see LOCKWOOD, P. A., (3) 848
DIZON, E. S., see KIENLE, R. N., (4) 996
DOGADKIN, B. A., see DONTSOV, A. A. (3) 721
DONTSOV, A. A., S. P. NOVITSKAYA, AND B. A. DOGADKIN, Study of sulfur vulcanization of brominated ethylene propylene rubber, (3) 721
DRAVES, C. Z., JR., Z. S. LEE AND L. SKOLNIK, Survey of tire cord candidates for radial tire belts (Abstract), (3) 851
DROZDOVSKII, V. F., see RAZGON, D. R., (3) 668
DUNCAN, J. S., see ELMER, O. C., (4) 923

EKERT, C. F., see KIENLE, R. N., (4) 996
EDMUNDS, W. M., see LOCKWOOD, P. A., (4) 946
ELMER, O. C. AND J. S. DUNCAN, Peroxide-cocatalyst curing systems for saturated polypropylene ether urethane elastomers, (4) 923
EVANS, C. W., Review of present and future continuous vulcanization processes in Europe (Abstract), (3) 839

FARLIE, E. D., Creep and stress-relaxation of natural rubber vulcanizates. Part I. Effect of crosslink density on the rate of creep in different vulcanizing systems, (3) 707
FILMONOVA, G. D., see LEZHNEV, N. N., (5) 1282
FLISI, U., A. VALVASSORI, AND G. NOVAJRA, Thermoelasticity and stress induced crystallization of EPDM elastomers (4) 1093
——, see ZAMBONI, V., (4) 1109
FOLAND, D. L. AND J. G. ANTHONY, L. C. M. vulcanization methods (Abstract), (3) 838
FOLT, V. L., R. W. SMITH, AND C. E. WILKES, Crystallization in a capillary rheometer. I., (1) 1
FORD, B. W. AND W. C. WARNER, A new dynamic test device for vulcanized rubber, (1) 249
FORRESTER, J. R., JR., see RUSCH, K. C., (5) 1440
FRISCH, H. L., see KLEMPNER, D., (3) 607
FRISCH, K. C., see KLEMPNER, D., (3) 607
FUJIMOTO, K., see FUJIWARA, S., (5) 1273
FUJIWARA, S. AND K. FUJIMOTO, NMR study of vulcanized rubber, (5) 1273
FURUTA, I., see NINOMIYA, K., (5) 1396

GARDNER, I. J., C. COZEWITH, AND G. VER STRATE, Infrared determination of composition of ethylene-propylene copolymers, (4) 1015
GASHTOL'D, N. S., see SIDOROVICH, E. A., (1) 166
GENT, A. N., see CHARRIER, J. M., (5) 1380
GESCHWIND, D. H. AND W. F. GRUBER, Tetramethylthiourea—a significant advance in curing of polychloroprene (Abstract), (5) 1449
GINGO, J. M., see BHAKUNI, R. S., (3) 846
GIUNCHI, G., see ZAMBONI, V., (4) 1109
GODA, K., see TSURUGI, J., (4) 857
GOEBEL, J. C. AND A. V. TOBOLSKY, Volume change accompanying rubber extension, (5) 1391
GREGG, R. A., The tensile strength of a glass yarn in rubber and the effects of moisture. I. (4) 937
GRIMM, G. W., see LOCKWOOD, P. A., (3) 848, (4) 946
GROSCH, K. A., Influence of polymer type on traction and wear of tires (Abstract), (5) 1437
GRUBER, W. F., see GESCHWIND, D. H., (5) 1449
GRUVER, J. T., see KRAUS, G., (3) 598; (5) 1297

HAAF, F. AND P. R. JOHNSON, The thermal and oxidative stability of chlorosulfonated polyethylene vulcanizates as measured by stress relaxation, (5) 1410
HAGAN, L., G. W. KUCKRO AND G. E. LORAND, Flame retardant, crosslinkable polyolefins designed for electrical insulation (Abstract), (5) 1440
HAGERMAN, E. M., Structure-property relationships in elastomer-modified terpolymer systems, (1) 62
HALL, W. E. AND H. C. JONES, The effect of zinc oxide and other curatives on the physical properties of a bus and truck compound (Abstract), (3) 841
HALLMAN, R. W., A. K. SHAH, AND K. C. MOORE, Compounding EPDM for low cost (Abstract), (5) 1435
HAMADA, M., see SATAKE, K., (5) 1173
HAMED, P. AND L. A. WALKER, Comparative properties of natural rubber and synthetic *cis*-1,4-polyisoprene (Abstract), (5) 1432
HARWOOD, J. A. C., A. R. Payne, AND R. E. WHITTAKER, An investigation into the high temperature strength and reinforcement of natural rubber, (3) 690
HAYAKAWA, K., see SATAKE, K., (5) 1173
HAZELTON, D. R. AND R. C. PUYDAK, Compounding EPDM for dynamics applications, (4) 1043
HECKMAN, F. A., see BOONSTRA, B. B., (5) 1451
HERZLICH, H. J., W. H. OSTRANLER, AND L. C. THOMPSON, Commercially acceptable EPsyn white sidewall, coverstrip sidewall compounds (Abstract), (5) 1437
HESS, W. M., C. E. SCOTT, AND J. E. CALLAN, Elastomer blends. Compatibility and relative response to fillers, (3) 814
——, see BURGESS, K. A., (1) 230
HIVELY, R. A., see PATEL, S. M., (5) 1439
HOESCHELE, G. K., see O'SHAUGHNESSY, F., (1) 52
HOLMES, T., see WILLIAMS, A. R., (5) 1439
HUGHES, L., see LEWIS, J. E., (3) 855
HUMPIDGE, R. T., A. MACLEAN, AND S. H. MORRELL, Micro-evaluation (Review), (2) 479

ILLINGER, J. L. AND N. S. SCHNEIDER, Low temperature dynamic mechanical properties of polyurethan polyether block copolymers (Abstract), (5) 1447
IPPEN, J., Formulation for continuous vulcanization in microwave heating systems, (1) 294

JANSSEN, M. L. AND J. D. WALTER, Strain measurements in bias, belted bias, and radial ply tires (Abstract), (5) 1453
JANZEN, J. AND G. KRAUS, Specific surface area measurement on carbon black (5) 1287
JEWELL, J. E., see LEWIS, J. E., (3) 855
JOHNSON, J. F., see CASALE, A., (2) 534
JOHNSON, P. R., see HAAF, F., (5) 1410
JONES, H. C., see HALL, W. E., (3) 841
JUDY, W. A., see SCOTT, K. W., (5) 1341

KALB, G. H. see BARNEY, A. L., (3) 660
KAPLAN, M. L. AND P. G. KELLEHER, Photoxidation of polymers without light: oxidation of polybutadiene and an ABS polyblend with singlet oxygen, (3) 642
KATZ, H. C., see BUCHANAN, R. A., (3) 842

KAUFMAN, S., W. P. SLICHTER, AND D. D. DAVIS, A nuclear magnetic resonance study of rubber-carbon black interactions (Abstract), (3) 843
KELLEHER, P. G., see KAPLAN, M. L., (3) 642
KHAN, A. A., see BARNEY, A. L., (3) 660
KIENLE, R. N., E. S. DIZON, T. J. BRETT, AND C. F. ECKERT, Treadwear and wet skid resistance of butadiene-styrene elastomers and blends, (4) 996
KIM, Y. K., see PIERCE, O. R., (5) 1350
KIRKHAM, M. C., The influence of precure dilation on the stress strain properties of EPDM networks, (5) 1326
——, see PRICE, C., (3) 744
KLEMPNER, D., H. L. FRISCH, AND K. C. FRISCH, Topologically interpenetrating elastomeric networks, (3) 607
KNABESCHUH, L. H., see LEIBU, H. J., (5) 1436
KOENIG, J. L., M. M. COLEMAN, J. R. SHELTON, AND P. H. STARMER, Raman spectrographic studies of the vulcanization of rubbers. I. Raman spectra of vulcanized rubbers, (1) 71
——, see STARMER, P. H., (3) 854
——, see SHELTON, J. R., (4) 904
KONDO, A. AND F. C. BRENNER, Research for a uniform quality grading system for tires. VI. Comparison of the effect of front and rear wheel drive vehicles on projected tread wear of a tire, (4) 960
——, see BRENNER, F. C., (1) 106; (4) 952
KRASILMIKOVA, M. K., see LEZHNEV, N. N., (5) 1282
KRAUS, G., A carbon black structure—concentration equivalence principle. Application to stress-strain relationships of filled rubbers, (1) 199
——, K. W. ROLLMAN, AND J. T. GRUVER, Dynamic properties of a model reinforced elastomer. Styrene-butadiene reinforced with polystyrene, (3) 598
——, and J. T. GRUVER, Thermal expansion, free volume, and molecular mobility in a carbon black filled elastomer, (5) 1297
——, see JANZEN, J. (5) 1287
KRISHEN, A., Quantitative determination of natural rubber, EPDM, and SBR in compounded cured stocks by pyrolysis gas chromatography (Abstract), (5) 1429
KUCKRO, G. W., see LAMONT, H., (5) 1440

LAKE, G. J. AND B. E. CLAPSON, Truck tire groove cracking-theory and practice, (5) 1186
LAMBERT, D. H. AND B. B. BOONSTRA, Abrasion resistance of pre-stressed and stressed rubber vulcanizates, (1) 214
LEE, Z. S., see DRAVES, C. Z., JR., (3) 851
LEHMICKE, D. J., Effect of twist and treating conditions on the physical properties of PET tirecords (Abstract), (3) 849
LEIBU, H. J., S. W. CAYWOOD, AND L. H. KNABESCHUH, A new EPDM for improved ozone resistance in blends with SBR and natural rubber (Abstract), (5) 1436
LEVINE, N. B., Carboxy nitroso rubber, chemistry, properties and applications, (1) 40
LEWIS, J. E., H. N. MERCER, M. L. DEVINEY, JR., L. HUGHES, AND J. E. JEWELL, Autoradiographic electron microscopy studies on elastomer systems. I. Experimental approach and preliminary results with gum and carbon black filled elastomer blends (Abstract), (3) 855
LEZHNEV, N. N., M. K. KRASILMIKOVA, K. A. YAKUKHINA, G. D. FILMONOVA, AND O. V. NIKITINA, The effect of aging on the reinforcing properties of carbon blacks, (5) 1282
LIVINGSTON, D. I., Influence of tire mechanics on traction and wear (Abstract), (5) 1446
LOCKWOOD, P. A., G. W. GRIMM, AND H. A. DEWHURST, Reinforced rubber composites (Abstract), (3) 848
——, W. M. EDMUNDS, AND G. W. GRIMM, Fatigue performance of tire belt cords, (4) 946
LORAND, G. E., see HAGAN, L., (5) 1440
LOWNE, R. W., The effect of road surface texture on tire wear, (5) 1159
LUB, S., see MOSCOU, L., (3) 805
LYONS, W. J., see PREVORSEK, D. C., (1) 271

MCCORMICK, W. E., Environmental health control for the rubber industry (Review) (2) 512
MACLEAN, A., see HUMPIDGE, R. T., (2) 479
MAHONEY, P., see WILSON, A., (5) 1434
MAREI, A. I., see SIDOROVICH, E. A., (1) 166
MARSH, P. A., A. VOET, T. J. MULLENS, AND L. D. PRICE, Electron micrography of interplanar spacings in carbon blacks. Part II (Abstract), (3) 844

MASTROMATTEO, R. P., J. M. MITCHELL, AND T. J. BRETT, J., New accelerators for blends of EPDM, (4) 1065
MAVRIGIAN, G., Mathematical notes concerning the tire contour integral, (1) 122
MAZOCCHI, A., Impregnated glass fiber rubber reinforcement (Abstract), (3) 848
MERCER, H. N., see LEWIS, J. E., (3) 855
MEREDITH, C. L., EPDM elastomers in rubber modified plastics, (4) 1130
MEYER, D. A. AND J. G. SOMMER, The effect of compositional and testing variations on the dynamic properties of compounds based on styrene butadiene and polybutadiene elastomers, (1) 258
MEZYNSKI, S. M. AND J. P. URBON, Passenger tire sidewall stress analysis (Abstract), (5) 1452
MICEK, E. J., see SCOTT, C. E., (5) 1445
MITCHELL, J. M., see MASTROMATTEO, R. P., (4) 1065
MOORE, K. C., see HALLMAN, R. W., (5) 1435
MORAN, A. L. AND D. B. PATTISON, A new dimension in the resistance of fluoroelastomers to compression set at high temperatures (Abstract), (3) 845
MORGANSTERN, K. H., Radiation vulcanization (Abstract), (3) 838
MORITA, E. AND J. J. D'AMICO, Rubber chemicals from cyclic amines. IV. Thiocarbamyl amine disulfide curing agents, (4) 881
——, see D'AMICO, J. J., (4) 889, 898
MORRELL, S. T., see HUMPIDGE, R. T., (2) 479
MORRISSEY, R. T., Halogenation of ethylene propylene hexadiene terpolymers, (4) 1025
MOSCOU, L., S. LUB, AND O. K. F. BUSSEMAKER, Characterization of carbon black structure by mercury penetration, (3) 805
MOZISEK, M., Radiotracer measurements of sulfur diffusion in rubbers, (5) 1307
MULLENS, T. J., see MARSH, P. A., (3) 844
MURAKAMI, K. AND S. TAMURA, Chemorheological treatment of crosslinked EPDM, (5) 1334
MURAKAMI, S., see TSURUGI, J., (4) 857
MURRAY, K., Thermally stable EPDM elastomers (Abstract), (5) 1441

NIKITINA, O. V., see LEZHNEV, N. N., (5) 1282
NINOMIYA, K. AND I. FURUTA, Interrelation between data from different physical tests, (5) 1396
NOVAJRA, G., see FLISI, U., (4) 1093
NOVITSKAYA, S. P., see DONTSOV, A. A., (3) 721

OBERTH, A. E., Effect and detection of loose chain ends in crosslinked polyurethane elastomers, (1) 152
OFSTEAD, E. A., see SCOTT, K. W., (5) 1341
O'SHAUGHNESSY, F. AND G. K. HOESCHELE, Hydrolytic stability of a new urethane elastomer, (1) 52
OSTRANDER, W. H. see HERZLICH, H. J., (5) 1437

PAGANO, C. A., see RANNEY, M. W., (4) 1080
PATEL, S. M. AND R. A. HIVELY, Gas chromatographic determination of mercaptobenzothiazole and benzothiazole (Abstract), (5) 1429
PATTISON, D. B., see MORAN, A. L., (3) 845
PAYNE, A. R. AND R. E. WHITTAKER, Low strain dynamic properties of filled rubbers (Review), (2) 440
——, see HARWOOD, J. A. C., (3) 690
PETERSEN, K. C., Ambient curing of unsaturated elastomers with halomethyl phenolic resins, (4) 914
PETERSON, J. E., JR., see RICHMOND, B. R., (5) 1450
PIERCE, O. R. AND Y. K. KIM, Fluorosilicones as high temperature elastomers, (5) 1350
PORTER, R. S., see CASALE, A., (2) 534
PREVORSEK, D. C. AND W. J. LYONS, Endurance of polymeric fibers in cyclic tension, (1) 271
PRICE, C., G. ALLEN, F. DECANDIA, M. C. KIRKHAM, AND A. SUBRAMANIAM, Stress-strain behavior of natural rubber vulcanized in the swollen state, (3) 744
PRICE, L. D., see MARSH, P. A., (3) 844
PUYDAK, R. C., see HAZELTON, D. R., (4) 1043
PYNE, J. R., Liquid rubbers-general rubber products technology, (3) 750

RANNEY, M. W. AND C. A. PAGANO, Silane coupling agent effects in ethylene propylene diene terpolymers, (4) 1080
RANSAW, A. C., see CARLSON, D. W., (5) 1278

RAZGON, D. R. AND V. F. DROZDOVSKII, Reaction of radical acceptors with polymer radicals formed by mechanical degradation of vulcanizates, (3) 668
REDDING, R. B. AND D. A. SMITH, Overall kinetics of natural rubber vulcanization at high temperatures. I., (5) 1316
RICHMOND, B. R. AND J. E. PETERSON, JR., Determination of wet and dry skid coefficients for blends of natural rubber and cis-polybutadiene (Abstract), (5) 1450
RIST, C. E., see BUCHANAN, R. A., (3) 842
RIVIN, D., Surface properties of carbon (Review), (2) 307
ROLLMANN, K. W., see KRAUS, G., (3) 598
ROSTLER, K. S. AND P. J. CASS, Published formulations and test data—the compounders heritage (Abstract), (5) 1448
ROWE, P. H. AND J. H. SUDEKUM, Applications compounding with a low Mooney EPDM (Abstract), (5) 1436
RUSCH, K. C., R. W. SANDERSON, AND H. VAN OENE, Dual-material molding of radial lip-type oil seals (Abstract), (3) 839
——, and J. R. FORRESTER, JR., Frictional characteristics of windshield wiper blades (Abstract), (5) 1440
RUSSELL, C. R., see BUCHANAN, R. A., (3) 842

SAMBROOK, R. W., Influence of temperature on the tensile strength of carbon filled vulcanizates, (3) 728
SANDERSON, R. W., see RUSCH, K. C., (3) 839
SATAKE, K., T. SONE, M. HAMADA, AND K. HAYAKAWA, Study of tire wear I. Correlation between laboratory abrasion tests and road tests, (5) 1173
SCHALLAMACH, A., How does rubber slide? (5) 1147
SCHNEIDER, N. S., see ILLINGER, J. L., (5) 1447
SCHWARZ, H. R., Fabric development for the rubber industry (Abstract), (3) 847
SCOTT, C. E., see BURGESS, K. A., (1) 230
——, see HESS, W. M., (3) 814
——, ——, V. E. CHIRICO, AND E. J. MICEK, Carbon black usage for treadwear and traction: a survey (Abstract), (5) 1445
SCOTT, G., Some new concepts in polymer stabilization, (5) 1421
SCOTT, K. W., N. CALDERON, E. A. OFSTEAD, W. A. JUDY, AND J. P. WARD, Polymers from cycloolefins, (5) 1341
SHAH, A. K., see HALLMAN, R. W., (5) 1435
SHAW, M. T. AND A. V. TOBOLSKY, Thermal stability of the carbon-carbon crosslink in polymer networks, (3) 579
SHELTON, J. R., J. L. KOENIG, AND M. M. COLEMAN, Raman spectroscopic studies of the vulcanization of rubbers. II. Raman spectroscopic studies as a function of cure time, (4) 904
——, see KOENIG, J. L., (1) 71
——, see STARMER, P. H., (3) 854
SHIH, C. K., Stress relaxation behavior of ethylene propylene diene terpolymers, (4) 1057
SIDOROVICH, E. A., A. I. MAREI, AND N. S. GASHTOL'D, High temperature relaxation transitions in elastomers, (1) 166
SIRCAR, A. K., see VOET, A., (1) 175
SKOLNIK, L., see DRAVES, C. Z., JR., (3) 851
SLICHTER, W. P., see KAUFMAN, S., (3) 843
SMITH, D. A., see REDDING, R. B., (5) 1316
SMITH, R. W., see FOLT, V. L., (1) 1
SMITHSON, F. D., Investigation of tire-road traction properties (Abstract), (5) 1447
SOMMER, J. G., see MEYER D. A., (1) 258
SONE, T., see SATAKE, K., (5) 1173
STARMER, P. H., J. L. KOENIG, J. R. SHELTON, AND M. M. COLEMAN, Raman spectroscopic studies of the vulcanization of rubbers. I. Raman spectroscopy of rubbers (Abstract), (3) 854
——, see KOENIG, J. L., (1) 71
STEWART, C. W., Nucleation and growth of bubbles in elastomers, (5) 1363
——, and J. J. VERBANC, The effect of varying the polymer composition on the cut growth characteristics of E/P/1,4-hexadiene tire treads, (5) 1203
STRECKER, R. A. H., Vulcanization of liquid polydienes with dithiols and peroxides, (3) 675
SUBRAMANIAM, A., see PRICE, C., (3) 744
SUDEKUM, J. H., see ROWE, P. H., (5) 1436

TAMURA, S., see MURUKAMI, K., (5) 1334
TANAKA, T., T. YOKOYAMA, AND Y. YAMAGUCHI, Methods for the determination of internal energy contribution to rubber elasticity, (1) 127
THIRION, P. AND R. CHASSET, Recent observations on the mechanical properties of polymer networks, (5) 1256
THOMPSON, L. C., see HERZLICH, H. J., (5) 1437
TOBOLSKY, A. V., see SHAW, M. T., (3) 579
——, see GOEBEL, J. C., (5) 1391
TRECKER, D. J., see COLOMB, H. O., JR., (3) 587
TSURUGI, J., S. MURAKAMI, AND K. GODA, Charge transfer complexing mechanism of antioxidants. Fate of aromatic amines during thermal oxidation of natural rubber vulcanizates, (4) 857

URBON, J. P., see MEZYNSKI, S. M., (5) 1452

VALVASSORI, A., see FLISI, U., (4) 1093
VAN OENE, see RUSCH, K. C., (3) 839
VEITH, A. G., Measurement of wet cornering traction of tires, (4) 962
VERBANC, J. J., see STEWART, C. W., (5) 1203
VER STRATE, G., see GARDNER, I. J., (4) 1015
VIAL, T. M., Recent developments in acrylic elastomers (Review), (2) 344
VOET, A., F. R. COOK, AND A. K. SIRCAR, Relaxation of stress and electrical resistivity in carbon-filled vulcanizates at minute shear strains, (1) 175
——, see MARSH, P. A., (3) 844
VORIH, W. J., Designing quiet tread spacings for tires (Abstract), (5) 1450

WADE, W. H. AND M. L. DEVINEY, JR., Adsorption and calorimetric investigations on carbon black surfaces. I. Immersional energetics of heat treated channel and furnace blacks, (1) 218
WALKER, L. A., see HAMED, P., (5) 1432
WALTER, J. D., see JANSSEN, M. L., (5) 1453
WARD, J. P., see SCOTT, K. W., (5) 1341
WARNER, W. C., see FORD, B. W., (1) 249
WHEELANS, M. A., Injection molding with natural rubber, (3) 620
WHITE, J. L., Biography of Melvin Mooney, (5) G 68
WHITTAKER, R. E., see PAYNE, A. R., (2) 440
——, see HARWOOD, J. A. C., (3) 690
WHITTINGTON, L. E., see DEVINEY, M. L., JR., (1) 87
——, see CORMAN, B. G., (5) 1430
WILKES, C. E., see FOLT, V. L., (1) 1
——, see CARMAN, C. J., (3) 781
WILLIAMS, A. R. AND T. HOLMES, Recent advances in study of tire to pavement interactions (Abstract), (5) 1439
WILSON, A. AND P. MAHONEY, Technique for evaluation of frictional properties of rubber sole and heel compounds (Abstract), (5) 1434
WISEMAN, W. A., Continuous curing with hot air (Abstract), (3) 838

YAKUZHINA, K. A., see LEZHNEV, N. N., (5) 1282
YAMAGUCHI, Y., see TANAKA, T., (1) 127
YANDELL, W. O., The use of a mechano-lattice analogy for determining the abrading stresses in sliding rubbers, (3) 758
YOKOYAMA, T., see TANAKA, T., (1) 127

ZAMBONI, V., U. FLISI, AND G. GIUNCHI, Crosslink density evaluation of EPDM vulcanizates, (4) 1109

SUBJECT INDEX

Abrasion, effect of asperity shape on, (3) 758
effect of road surface texture on, (3) 758
laboratory tests, comparison of, (5) 1173
correlation with road tests, (5) 1173
lattice analogy to predict, (3) 758
patterns, (5) 1451
resistance, effect of strain on, (1) 214
effect of pre-stress on, (1) 214
effect of stress on, (1) 214
rubber, factors affecting, (5) 1437
stresses in sliding rubber, (3) 758
Abstracts, papers presented at meetings of the Division of Rubber Chemistry, (3) 838; (5) 1429
Accelerators of sulfur vulcanization, 3-azabicyclo (3.2.2) non-3-yl-thiocarbonyl, 3 azabicyclo (3.2.2) non-3-yl sulfide as, (4) 889
3-azabicyclo (3.2.2) non-3-ylthiocarbonyl, azacycloheptyl sulfide as, (4) 889
3-azabicyclo (3.2.2) non-3-ylthiocarbonyl, di-t-butylamino sulfide as (4) 889
3-azabicyclo (3.2.2) non-3-ylthiocarbonyl, dimethylamino sulfide as, (4) 889
3-azabicyclo (3.2.2) non-3-ylthiocarbonyl, morpholino sulfide as, (4) 889
3-azabicyclo (3.2.2) non-3-ylthiocarbonyl, piperidino sulfide as, (4) 889
3-azabicyclo (3.2.2) non-3-ylthiocarbonyl, pyrrolidino sulfide as, (4) 889
azacycloheptylthiocarbonyl, 2-azabicyclo (3.2.2) non-3-yl sulfide as, (4) 889
azacyclononylthiocarbonyl, 3-azabicyclo (3.2.2) non-3-yl sulfide as, (4) 889
azacyclooctylthiocarbonyl, 3-azabicyclo (3.2.2) non-3-yl sulfide as, (4) 889
2-benzimidazolyl, N-morpholino disulfide as, (4) 898
2-benzoxazolyl, N-morpholino disulfide as, (4) 898
2-benzothiazolyl, N-morpholino disulfide as, (4) 898
2-(5-chlorobenzothiazolyl), N-morpholino disulfide as, (4) 898
dimethylaminothiocarbonyl, 3-azabicyclo (3.2.2) non-3-yl sulfide as, (4) 889
effect of amino groups on, (4) 889
effect of level on scorch of natural rubber, (4) 889
effect of solubility on blend properties, (4) 1065
effect of thiazole substituents on, (4) 898
effect on vulcanization of EPDM-nitrile rubber blends, (4) 1065
2-(6-ethoxybenzothiazolyl), N-morpholino disulfide as, (4) 898
high alkyl substitution in, (4) 1065
2-(4-methyl-5-acetylthiazolyl), N-morpholino disulfide as, (4) 898
2-(4-methyl-5-ethoxycarbonylthiazolyl) N-morpholino disulfide as, (4) 898
2-(4-methylthiazolyl), N-morpholino disulfide as, (4) 898
morpholinothiocarbonyl, 3-azabicyclo (3.2.2) non-3-yl sulfide as, (4) 889
2-(6-nitrobenzothiazolyl), N-morpholino disulfide as, (4) 898
pendent groups, (3) 771
as function of cure time, (3) 771
piperidinothiocarbonyl, 3-azabicyclo(3.2.2) non-3-yl-sulfide as, (4) 889
relative solubilities of, (4) 1065
synthesis of, (4) 889, 898
thiazole in high temperature vulcanization by sulfur, (5) 1316
Acetates, health hazard, (2) 512
Activation energy of carbon-carbon crosslink, breakdown, (3) 579
Adhesive bond strength, effect of EPDM grade on, (4) 1043
Adsorption, large molecules for determining surface area of particles, (5) 1287
polymer molecules by carbon black surface, (5) 1297
Aging, of carbon black (5) 1282
effect on reinforcing properties, (5) 1282
dynamic, oil migration during, (1) 87
effect on tear strength, (4) 1043
polypropylene ether glycol rubber, (4) 923
static, oil migration during, (1) 87
Akron abrader, in abrasion studies, (5) 1173
Alcohols, health hazard of, (2) 512
Amines, as antioxidants, (5) 1421
antioxidant activity of, (4) 857
antioxidant activity of oxidation intermediates of, (4) 857
primary, secondary, and tertiary, antioxidant activity of, (4) 857
Aminothiocarbonyl amine sulfides as accelerators, (4) 889
Aminothiocarbonyl amine disulfides as vulcanizing agents, (4) 881
Ammonium adipate, cure of polyacrylate rubbers by, (2) 344
Ammonium benzoate, cure of polyacrylate rubbers by, (2) 344
Analysis, of accelerators, (2) 381
of antioxidants, (2) 381
of amine antioxidants in vulcanizates, (4) 857
of polymers, (2) 381
of rubber vulcanizates by infrared and NMR spectroscopy, (5) 1278
by thin layer chormatography, (2) 381
Antioxidant, action during thermal oxidation of natural rubber vulcanizates, (4) 857
analysis of in vulcanizates, (4) 857

efficiency of oxidation intermediates of, (4) 857
efficiency of various, (4) 857
for EPDM, (5) 1441
fate of during autoxidation of vulcanizates, (4) 857
intermediates during oxidation, (4) 857
mechanism of, (4) 857; (5) 1421
metal ions as, (5) 1421
phenolic, (5) 1421
Antiozonant, leaching of from rubber compounds, (5) 1441
solubility in water, and effect of pH, (5) 1441
Apparatus, for dynamic testing of vulcnaized rubber, (1) 249; (2) 440
Dupont curve analyzer, (4) 904
forced vibration, (1) 249
for high frequency transmissibility, (2) 440
injection molding, (3) 620
laser Raman spectrometer, (4) 904
for measuring forces in a cornering tire, (4) 962
for mixing carbon black in liquid rubber, (3) 750
for stress relaxation measurement, (1) 185
for stress and strain under controlled environment, (4) 1109
for thermomechanical micro measurement, (2) 474
variable amplitude, (2) 440
Asperity, effect of shape on sliding rubber, (3) 758
Autooxidation, (4) 857; (5) 1421
3-Azabicyclo (3.2.2) non-3-ylsulfenyl chloride, (4) 881

Benzothiazole, determination of, (5) 1429
Benzothiazolinethione, determination of, (5) 1429
health hazard of, (2) 512
in Raman spectra of polybutadiene vulcanizate, (1) 71
Benzothiazolyldiethylthiocarbamyl sulfide, health hazard of, (2) 512
Benzothiazolyl disulfide, health hazard of, (2) 512
Benzothiazolyl monosulfide, (3) 771
Benzothiazolyl tetrasulfide, (3) 771
bis-N,N′ (2-benzothiazolylthiomethylene) urea, health hazard of, (2) 512
Bimodal molecular weight distribution, (1) 166
Biographical sketches, Gifford, J. H., (1) G8
Mooney, M., (5) G68
Osterhof, H. J., (3) G43
Bismuth dimethyldithiocarbamate, health hazard of, (2) 512
Blends of rubbers, analysis of, (5) 1278
carbon black dispersion in, (3(814, 826
compounding of, (4) 1065
differential thermal analysis of, (3) 814, 821
effect of accelerator solubility on vulcanizate properties of, (4) 1065
effect of halogenation on EPDM, (4) 1025
electron microscopy of, (3) 814
EPDM and nitrile rubber, (4) 1065
EPDM and other rubbers, (5) 1435, 1436
EPDM and polyisoprene, (4) 1109
Mooney-Rivlin constants for, (4) 1109
natural rubber and polybutadiene, skid resistance of, (5) 1450
oil migration in, (1) 87
oil diffusion coefficients in, (1) 87
tensile strength of, (4) 1065
tire tread wear and wet skid of, (4) 996
zone size of, (3) 814
Block copolymers, polyurethan-polyether, (5) 1447
Blowing in vulcanizates, nucleation of bubbles, (5) 1363
Book reviews, ABS Resin Manufacture, (2) G31
Adhesives Handbook, (2) G30
Advances in Macromolecular Chemistry, Vol. 2, (1) G12
Advances in Polymer Blends and Reinforcement: Conference, (1) G9
The analysis of Rubber and Rubber-Like Polymers, (2) G33
Block Polymers, (1) G11
Cellular Plastics-Recent Developments, (2) G31
Design Engineering Studies-Rubber Handbook, (1) G11
Engineering Plastics and Their Commercial Development, (1) G9
Engineering Properties of Thermoplastics, (1) G11
Epoxy Resins, (1) G10
Evaluation of Studded Tires, (1) G10
Flame Retardant Polymers, (2) G32
Flame Retardant Textiles, (1) G9
Markov Chains and Monte Carlo Calculations in Polymer Science, (1) G9
Metal Coating of Plastics, (2) G32
Principles of Polymer Systems, (2) G30
Report on the Role of Plastics in Solid Waste, (1) G10
Soundproofing Building Materials, (2) G31
Thermal Stability of Polymers, (2) G32
Viscoelastic Properties of Polymers, (1) G10
Bound rubber, nuclear magnetic resonance studies of, (5) 1273
Braking coefficient, variation with cornering coefficient, (4) 962
Brittleness temperature, (5) 1396
Bubbles in rubber, growth of, (5) 1363
homogeneous nucleation of (5) 1363
Butanediol-1, 4, curing agent for urethans, (1) 52
Butyl rubber, blends with various rubbers, (3) 814
damping by, (4) 1043
dielectric loss factor of, (1) 294
diffusion of oil in, (5) 1430
diffusion of sulfur in, (5) 1307

double strain amplitude and phase angle in, (2) 440
dynamic shear moduli of vulcanizates of, (1) 258
effect of aging on tear of, (4) 1043
effect of carbon black and plasticizer on dynamic properties of, (1) 258
effect of carbon black loading on tensile stress relaxation of, (1) 185
effect of mill size on mixing of, (2) 440
friction of, (5) 1147
health hazard in manufacture of, (2) 512
in-phase and out-of-phase response of, (2) 440
low temperature flexibility of, (4) 1043
oil diffusion coefficient-concentration function, (1) 87
resin curing of, (4) 914
shear modulus and double strain amplitude, (2) 440
spring rate of, (4) 1043
tensile strength retention of inner tubes of, (2) 397
transmissibility of, (2) 440
Bylaws of the Division of Rubber Chemistry, (1) G13

C_1 and C_2 values, see Mooney-Rivlin constants
Cadmium diethyldithiocarbamate, health hazard of, (2) 512
Carbon-13, nuclear magnetic resonance spectroscopy, (3) 781
Carbon-14, accelerators labelled by, (3) 771
oil labelled by, (1) 87
Carbon black, abrasion studies of HAF-HS and ISAF, (5) 1173
acidic groups on surface of, (2) 307
adsorption by, (1) 218
adsorption from solution by, (2) 307
aggregate structure of, (2) 307
aging of, (5) 1282
basal layer planes in, (2) 307
in blends of rubber, (3) 814
bonding to rubber, (1) 175
chemisorption of, (2) 307
compressed and oil absorption, (1) 199
computer data processing of particle size of, (1) 230
concentric layer orientation, (2) 307
continuous graphitic layer network, (1) 230
dibutyl phthalate absorption of compressed, (1) 199
dielectric loss factor, (1) 294
differential heats of adsorption on, (1) 218
dispersion in liquid rubber, (3) 750
effect of black type on dielectric heating, (1) 294
effect on crystallization of natural rubber in a capillary rheometer, (1) 29
effect on damping coefficient, (1) 258
effect of densification on modulus conferred by, (1) 199
effect on double strain amplitude and dynamic modulus, (2) 440
effect on dynamic complex spring rate, (1) 258
effect of graphitization on abrasion, (1) 214
effect of heat treatment temperature on, (2) 307
effect on isothermal and adiabatic tensile strength of rubbers, (2) 397
effect of loading on shear stress relaxation of SBR, (1) 175
effect of loading on tire treadwear and traction, (5) 1445
effect of mixing conditions on dispersion of, (3) 750
effect of particle size on strain relaxation rate minima, (1) 185
effect on phase angle in Butyl rubber, SBR, and natural rubber, (2) 440
effect on relaxation rate of SBR of surface area of, (1) 185
effect on shear complex modulus, (1) 258
effect on shear elastic modulus, (1) 258
effect on shear loss modulus, (1) 258
effect on static spring rate, (1) 258
effect of storage on, (5) 1282
effect of surface area modulus, (2) 440
effect on tensile stress relaxation of SBR of loadings of, (1) 185
effect of type on tire treadwear and traction, (5) 1445
effect on vulcanization, (1) 199
effective loading by, (1) 199
electron micrographs of, (2) 307
electron microscopy of, (3) 844
an environmental control, (2) 512
form factor related to rubber properties, (1) 230
graphon, see Graphitized carbon black
heats of adsorption of, (2) 307
heat treated, (2) 307
heterogeneous nature of surface of, (1)218
hydrogen atoms on surface of, (2) 307
hydroxyl groups on surface of, (2) 307
immersional calorimetry of, (1) 218
lactone groups on surface of, (2) 307
microstructure of, (2) 307
migration in rubbers, (1) 185
morphology, (1) 230; (2) 307
occluded rubber in, (3) 728
oxidation of, (5) 1282
oxidized, (2) 307
packing density, (1) 199
paracyrstalline graphitic layer structure, (1) 230
pi-electrons on surface of, (2) 307
pyrolytic volatile analyses of, (2) 307
quinone groups on surface of, (2) 307
reinforced rubber, nuclear magnetic resonance studies of, (5) 1273
structure of rubber phase, (5) 1273
SBR, (5) 1208, 1227, 1249
thermal expansion of, (5) 1297
shear relaxation of electrical resistivity of, (1) 175
rupture of rubber bonding to, (1) 185
shift factors for equivalence of, (1) 199

strain magnification and relaxation rate by (1) 185
structure, concentration equivalence, (1) 199
effect of crosslinking on shift factor of, (1) 199
effect on dynamic properties, (2) 440
effect on strain shear stress functions, (1) 175
effect of strain on shift factor of, (1) 199
effect of temperature on shift factor of, (1) 199
index of (3) 805
by mercury porosimetry, (3) 805
and occluded volume, (1) 199
shift factor for, (1) 199
shift factor in EPDM rubber, (1) 199
shift factor in styrene butadiene rubber, (1) 199
structure-volume loading reduction, (1) 199
surface, change during aging of, (5) 1282
surface area measurement, (5) 1287
surface areas measured by various methods, (2) 207
surface chemistry of, (2) 307
surface properties of, (2) 307; (5) 1282
surface reactions of, (2) 307
transient structure change and resistivity, (1) 175
transient structure change and shear stress, (1) 175
unit and domain dimensions of, (1) 230
void volume in, (1) 199
Carbon to carbon crosslink, Arrhenius activation energies of, (3) 579
thermal stability of, (3) 579
variation of stability of, (3) 579
Carbon-rubber gel, (5) 1208, 1227, 1249
Carbon tetrachloride, health hazard, (2) 512
Carboxynitroso rubber, (1) 40
oxidation resistance, (1) 40
solvent resistance, (1) 40
Catalase antioxidant, (5) 1421
Catalysts, ring opening polymerization, (5) 1341
Chain extension, liquid rubbers and, (3) 750
Chemorheology of EPDM vulcanizates, (5) 1334
Chlorobutyl rubber, blends with various rubbers, (3) 814
tensile strength retention of innertubes of, (2) 397
Chlorosulfonated polyethylene, maleimide cures of, (5) 1410
stability of vulcanizates, (5) 1401
stress relaxation of vulcanizates of, (5) 1410
Chromatography of rubber chemicals, (2) 381
Chromium trifluoroacetate, vulcanizing agent for carboxynitroso rubber, (1) 40
Clay, dynamic properties in rubber, (2) 440
dynamic properties in water, (2) 440
silane treated, (5) 1436
Coefficient of friction, effect of temperature on, (2) 397
Compresion set, micro size, (2) 479
Computer program, mechano-lattice analogy of sliding rubber, (3) 758
Conductivity, electrical, effect of dynamic properties, (2) 440
Continuous vulcanization, high temperature, (5) 1316
Copolymerization theory, (3) 771
Copper ions, as antioxidant, (5) 1421
Cornering stability, (5) 1456
Crack growth tests, laboratory, (5) 1186
Creep, crosslink density and, (3) 707
crosslink length and, (3) 707
extranetwork material and, (3) 707
main chain modification and, (3) 707
measurement of, (3) 707
natural rubber, (3) 707
polymer networks, (5) 1256
Critical rate of shear, (1) 1, 12, 29
Crosslink, trifunctional, (1) 152
Crosslink density, effect on breaking energy, (3) 690
effect on creep rate, (3) 707
effect on stress relaxation, (3) 579, 707
in EPDM, (3) 653; (4) 1109
in interpenetrating networks, (3) 607
measurement of, (3) 707; (5) 1316
measurement by Flory-Huggins equation, (4) 1109
measurement by Mooney-Rivlin equation, (4) 1109
nuclear magnetic resonance measurement, (5) 1273
variation of stability of, (3) 579
Crosslink distances in vulcanized rubber, NMR measurements, (5) 1273
Crosslink distribution, (3) 771
Crosslinking, see Vulcanization
Crystallization of rubber, in a capillary rheometer, (1) 1, 12, 29
effect of acetone extract from natural rubber on, (1) 29
effect of carbon black on, (1) 29
effect of ethylene sequential homogeneity in EPDM, (4) 1093
effect of microstructure on, (1) 12
effect of molecular weight on, (1) 12
effect of oil on, (1) 29
effect of stearic acid on, (1) 29
effect of temperature on, (1) 1
electron micrographs of, (1) 1
of natural rubber, (1) 1, 12, 29
orientation and, (1) 1
of polyisoprene, (1) 12, 29
stress induced in EPDM, (4) 1093
CTAB adsorption test of carbon black surface area, (5) 1287
Cure rates, of accelerators, (4) 889, 898
of vulcanizing agents, (4) 881, 898
Cure time, micromeasurement of, (2) 479
Curing, see Vulcanization
Cut growth, EPDM, (5) 1203

Cyclohexene, radiation crosslinking at sites of, (3) 587
Cyclohexyl benzothiazole sulfenamide, carbon-14 labelled, (3) 771
Cyclohexyl phenyl-p-phenylenediamine, antioxidant activity of, (4) 857
oxygen absorption of vulcanizates containing, (4) 857
Cyclooctene, polymerization of, (5) 1341
Cyclooctadiene, polymers from, (5) 1341
Cycloolefins, polymers from, (5) 1341

Damping, by Butyl rubber, (4) 1043
by EPDM, (4) 1043
by natural rubber, (4) 1043
effect of process oil on, (4) 1043
Damping coefficient, effect of carbon black loading on, (1) 258
effect of crosslinking on, (1) 258
of vulcanizates of styrene butadiene rubber, (1) 258
Deformation of rubber tubes, (5) 1380
Degradation of rubber, mechanical, capillary effect, (2) 534
effect of concentration, (2) 534
effect of pressure, (2) 534
effect of solvent, (2) 534
effect of temperature, (2) 534
reaction scheme, (2) 534
shear methods, (2) 534
Degradation mechanism of rubber, chemical, (2) 534
effect of concentration, (2) 534
effect of pressure, (2) 534
effect of solvent, (2) 534
effect of temperature, (2) 534
reaction scheme, (2) 534
shear methods, (2) 534
Dicyclopentadiene dioxide, curative for carboynitroso rubber, (1) 40
Dibutylamine, health hazard of, (2) 512
Di-(t-butylphenol) disulfide, radical trap, (3) 688
Dielectric heating, for continuous vulcanization, (1) 294
effect of loss factor on, (1) 294
effect of polar compounds on, (1) 294
Diethylene glycol, effect on dielectric heating, (1) 294
Differential thermal analysis of rubber blends, (3) 814
Diffusion in rubber of aniozonants, (5) 1441
coefficients of rubber blends, (1) 87
concentration dependence, (1) 87
effect of flexing on, (1) 87
of extender oils, (5) 1430
of oil, coefficient of, (1) 87
of sulfur, temperature dependence, (5) 1307
2, 5 Dihydrothiophene, Raman spectrum of, (1) 71
Di (isooctylphenol) disulfide, as radial trap, (3) 668
Dimethyl-2-naphthylamine, antioxidant activity of, (4) 857
oxygen absorption of vulcanizates containing, (4) 857
Diphenylmethane-4, 4′-diisocyanate, urethane formation with, (4) 923
urethane formation with polypropylene ether glycol, (4) 923
Disulfides, tetraalkylthiuram, (4) 1065
bis(dodecylisopropylthiuram), (4) 1065
bis(octadecylisopropylthiuram), (4) 1065
Dithiocarbamates, metal alkyl, (4) 1065
accelerators of EPDM-nitrile rubber blends, (4) 1065
relative solubility of, (4) 1065
Di-o-tolylguanidine, health hazard of, (2) 512
Di(trichlorophenyl) sulfide, as radical trap, (3) 668
Division of Rubber Chemistry, bylaws (1) G13
future meetings, (1) G2; (2) G28; (3) G40 (4) G54; (5) G
future meeting symposia, (1) G3; (2) G29; (3) G41; (4) G55; (5) G
library information service, (1) G2; (2) G28; (3) G40; (4) G54; (5) G
officers and executive committee, (1) G1; (2) G27; (3) G39; (4) G53; (5) G
program for Fall meeting, (4) G57
program for Spring meeting, (1) G4
steering committee, (1) G1, (2) G27; (3) G39; (4) G53; (5) G
Double strain amplitude, effect of chemical promotors, (2) 440
effect of frequency, (2) 440
effect of mixing time, (2) 440
effect of temperature, (2) 440
in-phase and out-of-phase, (2) 440
and phase angle, (2) 440
and shear modulus, (2) 440
Dynamic modulus, temperature variation of perfluororubbers, (3) 660
frequency function for perfluororubbers, (3) 660
Dynamic properties, and carbon black, (2) 440
of carbon black in paraffin oil, (2) 440
chemical promoters and, (2) 440
of clay in rubber, (2) 440
of clay in water, (2) 440
domain model for, (2) 440
effect of frequency on, (2) 440
effect of mixing on, (2) 440
effect of temperature on, (2) 440
effect of vulcanization degree on, (2) 440
and electrical conductivity, (2) 440
of filled rubbers, (2) 440
of phenyl-2-naphthylamine in rubber, (2) 440
of polyurethane-polyether block copolymers, (5) 1447
of rubber network, factors affecting, (5) 1256
and stiffness, (2) 440
test apparatus for, (1) 249; (2) 440
and tire heat buildup, (2) 440
variation with strain, (2) 440

Elastic modulus, see Storage modulus
Elastic theory, (1) 127, 152
Electrical insulation, flame retardant, (5) 1440
non-chlorine containing, (5) 1440
Electrical resistivity, activation energy of relaxation of, (1) 175
effect of rubber type on relaxation of, (1) 185
relation to reinforcement of filled SBR, (1) 175
relaxation of, (1) 175
relaxation as function of temperature, (1) 175
relaxation of filled SBR as function of strain, (1) 175
reversible relaxation, (1) 175
Electron acceptor function of carbon black, (2) 307
Electron donor function of carbon black, (2) 307
Electron microscopy, autoradiographic studies on gun and carbon black filled rubber, (3) 855
of blends of various rubbers, (3) 814
of carbon black, (2) 307; (3) 844
surface area by, (5) 1287
Electron paramagnetic resonance, of radicals from mechanical degradation, (3) 668
Energy input to break (rubber), (3) 690
effect of crosslink density, (3) 690
effect of hysteresis, (3) 690
effect of strain, (3) 690
effect of temperature, (3) 690
Entanglement of rubber chains, (5) 1256
effect on stress strain properties, (5) 1208, 1227
effect of swelling of vulcanizates, (5) 1208, 1227
effect of vulcanization of swollen rubber on, (3) 744
EPDM, see Ethylene propylene rubber
Ethylene dichloride, health hazard of (2) 512
Ethylene propylene reactivity ratio product, (3) 711
Ethylene propylene rubber, accelerators for vulcanization of, (4) 1065
analysis by infrared spectroscopy, (4) 1015
analysis by radioassay, (4) 1015
as antiozonant, (5) 1436
blends with other rubbers, (3) 814; (5) 1435, 1436
bonding to metal of, (4) 1043
brominated, (3) 721
dehydrobromination of, (3) 721
hydrogen sulfide evolution during, (3) 721
vulcanization of, (3) 721
carbon 13 nuclear magnetic resonance assignments, (3) 781
carbon 13 NMR spectroscopy of, (3) 781
chemorheology of, (5) 1334
comparison of chlorination and bromination, (4) 1025
composition, accurate measure of, (4) 1015
compounding for low cost, (5) 1435
crosslink density of, (4) 1109
crystallization of, (4) 1093
crystallization as a function of composition, (4) 1093
cure compatibility by halogenation, (4) 1025
dehydrohalogenation of halogenated, (4) 1025
determination in blends, (5) 1429
dielectric loss of, (1) 294
dynamic shear moduli of vulcanizates, (1) 258
effect of black loading on spring rate, (4) 1043
effect of black type on spring rate of, (4) 1043
effect of composition on analysis, (4) 1015
effect of composition on fatigue resistance, (5) 1203
effect of diene content on shear creep, (4) 1043
effect of ethylene content on Mooney-Rivlin constants, (4) 1109
effect of ethylene sequential homogeneity on, (4) 1093
effect of ethylene sequential homogeneity on green strength, (4) 1093
effect of grade on adhesive bond strength, (4) 1043
effect of grade on spring rate, (4) 1043
effect of halogenation, on adhesion of, (4) 1025
on blends with, (4) 1025
on ozone attack on, (4) 1025
effect of heat aging on tear strength of, (4) 1043
effect of mill size on mixing, (2) 479
effect of precure dilation on newtork, (5) 1326
effect of strain on crystallization of, (4) 1093
effect of termonomer on halogenation, (4) 1025
enthalpy of, (4) 1093
friction of (5) 1440
graft of styrene and acrylonitrile onto, (4) 1130
color stability of, (4) 1130
effect of EPDM termonomer on, (4) 1130
effect of rubber content on impact strength, (4) 1130
effect of solvent system on, (4) 1130
effect of termonomer concentration on, (4) 1130
impact strength of, (4) 1130
molding of, (4) 1130
process stability of, (4) 1130
thermal stability of, (4) 1130
weather resistance of (4) 1130
halogen attack on allylic hydrogen atoms, (4) 1025

halogenation, (4) 1025
effect on rubber to metal adhesion of, (4) 1025
health hazard in manufacture of, (2) 512
hexadiene terpolymer, effect of composition on stress relaxation, (4) 1057
effect of ethylene content on melt flow of, (4) 1057
effect of temperature on modulus, (4) 1057
effect of temperature on relaxation, (4) 1057
fatigue resistance of, (5) 1203
melting as function of composition, (4) 1057
relaxation of, (4) 1057
relaxation modulus, (4) 1057
relaxation rate of, (4) 1057
high frequency isolation by, (4) 1043
hydrogenated polyisoprene as model of, (4) 1093
infrared of, (4) 1015
loss tangent of, (4) 1043
low temperature flexibility of, (4) 1043
low viscosity, (5) 1436
monomer sequence in, (3) 781
monosulfidic crosslinks in sulfur vulcanizates of, (5) 1334
Mooney-Rivlin constants for, (4) 1109
oil diffusion coefficient-concentration function, (1) 87
oil extended, (5) 1435
peroxide cure of, (5) 1334
phase angle tangent of vulcanizates of, (1) 258
polymer-benzene interaction parameter, (4) 1109
polysulfidic crosslinks in vulcanizates, (5) 1334
radioactive ethylene in, (4) 1015
radioactive propylene in, (4) 1015
reactivity ratio product for, (3) 781
shift factor for carbon black equivalence in, (1) 199
silane coupling agents and, (4) 1080
specific heat of, (4) 1093
spring rate of, (4) 1043
stress-induced crystallization, (4) 1093
stress relaxation of, (5) 1334
stress strain properties of, (5) 1326
tear strength of, (4) 1043
tensile strength as function of halogen content, (4) 1025
thermal stability improvement of, (5) 1441
thermodynamic behavior of, (4) 1093
thermoelastic behavior, (4) 1093
in tires, groove cracking, (5) 1203
treadwear, (5) 1203
vinylcyclohexene terpolymer, (3) 653
catalyst for, (3) 653
crosslink density of, (3) 653
preparation of, (3) 653
vulcanization of, (3) 653
whiteside wall coverstrip, (5) 1437
windshield wiper blade from (5) 1440
Extension of rubber, volume during, (5) 1391

Fabrics for rubber industry, (3) 847
Failure properties of rubber, (5) 1396
Fatigue of glass cord belts, (4) 946
effect of cord impregnant, (4) 946
effect of cord twist, (4) 946
effect of fiber diameter, (4) 946
effect of rubber on, (4) 946
effect of stress-compression cycle, (4) 946
Fatigue, tread rubber, (5) 1186
Fibers, glass, (3) 846; (4) 946
reinforcement by, (3) 846
rheology of, (3) 846
Fibers, synthetic, fatigue life, (1) 271
effect of activation energy of growth (1) 271
effect of force amplitude (1) 271
effect of fracture surface energy, (1) 271
effect of frequency, (1) 271
effect of modulus, (1) 271
effect of morphology, (1) 271
effect of strain amplitude, (1) 271
effect of temperature, (1) 271
and endurance, (1) 271
and law of cumulative damage, (1) 271
and molecular chain breakage, (1) 271
Filler, injection molding and, (3) 620
Filler aggregates, (5) 1249
Flame retardant electrical insulation, (5) 1440
Flexibility, low temperature, (4) 1043
Flory function, (5) 1208, 1227
Flory-Huggins equation, (4) 1109
EPDM and, (4) 1104
Fluoroelastomer, new, (3) 845
compression set, (3) 845
Fluorosilicone, (5) 1350
high temperature use, (5) 1350
preparation of, (5) 1350
properties of, (5) 1350
shear modulus, (2) 479
Foams, homogeneous nucleation of bubbles, (5) 1363
Force analysis, tires, (5) 1456
Force-temperature coefficient, (1) 127
natural rubber and, (1) 127
polyurethane, (1) 127
Fracture mechanics of vulcanizates, (5) 1186
Free volume, carbon black loaded rubber, (5) 1297
Friction, coefficient of, (4) 962
peak, (5) 1450
sliding, (5) 1450
Friction, hysteretic stresses in, (3) 758
prediction of hysteretic stresses, (3) 758
modes of, (4) 962
wet tires, (4) 962
of EPDM, (5) 1440
Friction of rubber, dynamic, (5) 1147
effect of compound variations, (5) 1443
effect of polymer variations, (5) 1443
mechanism of, (5) 1147

static, (5) 1147
wave of detachment in, (5) 1147
Friction of shoe soles and heels, (5) 1434
Friction of tires, factors in, (5) 1447
Frictional heat in tires, (2) 397

Gas chromatography, in rubber analysis, (5) 1429
Gaskets, EPDM, (5) 1436
Gaussian modulus, (5) 1326
Glass, belts in tires, (4) 946
cords in tires, (4) 946
Glass transition temperature, butadiene butadiene styrene rubber, (4) 996
effect of carbon black, (5) 1297
effect on tire wear, (4) 996
Goodyear, Charles, medalist, 1971-H. Judson Osterhof, (3) G43
address, (3) G45
Grant-Paul relationships, (3) 781
Graphitized carbon black, adsorption by, (2) 307
chemisorption by, (2) 307
heats of adsorption on, (2) 307
in rubber vulcanizates, (5) 1208, 1227, 1249
shear stress relaxation of SBR loaded with, (1) 175
surface area of, (2) 307
tensile stress relaxation of SBR loaded with, (1) 185
Green strength, of cis polyisoprene, (5) 1432
effect of ethylene sequential homogeneity in EPDM on, (4) 1093
Groove cracking of tires, EPDM, (5) 1203
mechanism of, (5) 1186
truck tires, (5) 1186
Guide for authors, (2) G33

Hardness, micro size, (2) 479
Hazard, to health from various rubber chemicals, (2) 479
Health control, (2) 512
Heats of adsorption of carbon blacks, (2) 307
Heat buildup, (5) 1396
Heat resistant compounds, EPDM, (5) 1441
Heels, friction of, (5) 1434
Hexamethylenetetramine, health hazard of, (2) 512
High temperature, rubbers, (5) 1350
reinforcement of natural rubber, (3) 690
strength of natural rubber, (3) 690
Hydrocarbons, paraffinic, aromatic, and chlorinated, environmental control, (2) 512
Hydrogen sulfide, kinetics of evolution during vulcanization, (3) 721
Hypalon, see Chlorosulfonated polyethylene
Hysteresis, reduced, of natural rubber, (3) 690

Identification of chemicals in rubber compounds, (2) 381
accelerators, (2) 381
antioxidants, (2) 381
polymers, (2) 381
Iodine number, ASTM, for measuring surface area, (5) 1287
Inflated rubber structures, (5) 1380
Infrared, analysis of vulcanizates, (5) 1278
detectors for thermometry by, (2) 397
thermometry, (2) 397
wavelength sensitivity for heat, (2) 397
Information retrieval, rubber compound formulation in literature, (5) 1448
Injection molding, compounds
EV systems, (3) 620
Extenders in, (3) 620
fillers in, (3) 620
scorch time, (3) 620
effect of barrel temperature, (3) 620
effect of curvatives, (3) 620
effect of injection pressure, (3) 620
effect of mold temperature, (3) 620
effect of nozzle diameter, (3) 620
effect of nozzle temperature, (3) 620
effect of screw speed, (3) 620
effect of screw back pressure, (3) 620
equipment, (3) 620
high temperature vulcanization for, (5) 1316
of natural rubber, (3) 620
properties of vulcanizates from, (3) 620
Insulation, electrical, (5) 1436
Interpenetrating rubber networks, (3) 607
crosslink density in, (3) 607
Isomerism, cis-trans, during vulcanization, (1) 71; (4) 904
Isopropoxydiphenylamine, antioxidant activity of, (4) 857
oxygen absorption of vulcanizates containing, (4) 857

Ketones, health hazard of, (2) 512
Kinetics of rubber vulcanization, (5) 1316
Kinetic theory of rubber elasticity, (5) 1391

Lambourn abrader, (5) 1173
Laser beam, in Raman spectroscopy, (1) 71
Lattice, mechano analogy in sliding rubber, (3) 758
Lead dimethyldithiocarbamate, health hazard of, (2) 512
Lead dithiocarbamate, health hazard of, (2) 512
Linear thermal expansion coefficient for rubbers, (1) 127
Linkage reinforcement of rubber, (5) 1208, 1227, 1249
Liquid crystals, measurement of tire surface temperature by, (2) 397
Liquid rubber, aging, (3) 675
antioxidants in, (3) 675
carbon black dispersion, (3) 750
carbon black types in, (3) 750
compounding, (3) 750
curing systems, (3) 754
gel point, (3) 675
microstructure, (3) 675
mixing conditions for, (3) 754
peroxides in vulcanization, (3) 675

cis polybutadiene, (3) 675
polybutadiene, (3) 675
polyisoprene, (3) 675
resin curing of, (4) 914
technology, (3) 750
tensile strength of vulcanized, (3) 675
thiols in vulcanization, (3) 675
vulcanization, (3) 675
Loss factor, and dielectric heating, (1) 294
as function of temperature, (1) 294
of various rubbers, (1) 294
Loss modulus, effect of temperature, (3) 598
of polystyrene reinforced SBR, (3) 598
Loss tangent, effect of crosslinking on temperature dependence of, (1) 166
effect of molecular weight on maximum of, (1) 166
effect of temperature on, (1) 166
function of molecular weight, equation for, (1) 166
Lubrication, boundary, (4) 962
elastohydrodynamic mode, (4) 962
hydrodynamic, (4) 962

Maleimide, crosslinking of chlorosulfonated polyethylene by, (5) 1410
vulcanizate stability, (5) 1410
Mechanical degradation, formation of radials by, (3) 668
Mechanical properties, interrelations among, (5) 1396
of rubber networks, (5) 1256
Mechanochemistry, (2) 534
Medical application of silicone rubber, (2) 363
Meetings, Division of Rubber Chemistry, (1) G4; (4) G57
Mercaptobenzothiazole, see Benzothiazolinethione
Mercaptoimidazoline, health hazard of, (2) 512
curvature for acrylic elastomers, (2) 344
4,4′-Methylene bis chloroaniline, (1) 52
Methylene dianiline, (1) 52
2-Methyl-2-octene, adsorption by carbon black, (1) 307
N-(2-Methyl-2-nitropropyl)-4-nitrosoaniline, modifier of cis polyisoprene, (5) 1432
Microevaluation of rubber properties, (2) 479
Microhardness, (2) 479
Microstructure of rubber vulcanizates, (5) 1278
Microwave heating, in continuous vulcanization, (1) 294
effect of loss factor on, (1) 294
Migration, see Diffusion
Mill size, effect on mixing, (2) 479
effect on shear modulus, (2) 479
Mixing, effect on shear modulus, (2) 479
mill size and, (2) 479
of various rubbers, (2) 479
Molding, dual material, (3) 839
Molecular mobility, in carbon black loaded rubber, (5) 1297
Molecular structure, use to study oil diffusion, (5) 1430
Molecular weight, limit for polymer breakdown, (2) 534
Mooney, Melvin, biography, (5) G68
Mooney-Rivlin constants, (5) 1208, 1227
effect of crosslink density on, (4) 1109
effect of EPDM-polyisoprene blends, (4) 1109
effect of ethylene content of EPDM on, (4) 1109
effect of fillers on, (4) 1109
effect of strain amplification factor, (4) 1109
effect of temperature of EPDM on, (4) 1109
of natural rubber, (3) 707
significance of C_2, (4) 1109
Mooney-Rivlin equation, (1) 127; (4) 1109; (5) 1326, 1391
effect of EPDM composition on results from, (4) 1109
effect of EPDM-polyisoprene blend, (4) 1109
EPDM and, (4) 1109
Morpholinosulfenyl chloride, (4) 881, 898
Mullins effect, (5) 1208, 1227, 1249

Natural rubber, accelerator pendent group on vulcanizates of, (3) 771
action of antioxidants in vulcanizates of, (4) 857
analysis of, in blends, (5) 1429
blend with halogenated EPDM, (4) 1025
blends with various elastomers, (3) 814
capillary flow as a function of force and rate, (1) 1
comparison with cis polyisoprene, (5) 1432
crosslink distribution in vulcanizates, (3) 707
crystallization of, (1) 1, 12, 29
effect of aging of black-rubber mixes on, (1) 29
effect of capillary geometry on, (1) 1, 12, 29
effect of carbon black on, (1) 29
effect of fatty acid on, (1) 29
effect of microstructure on, (1) 12
effect of molecular weight on, (1) 12, 29
effect of oil on, (1) 29
effect of temperature on, (1) 12, 29
damping by, (4) 1043
dielectric loss factor of, (1) 294
effect of aging on tear of, (4) 1043
effect of carbon black on double strain amplitude and dynamic modulus, (2) 440
effect of carbon black loading on tensile stress relaxation, (1) 185
effect of mill size on mixing, (2) 479
electron micrographs of crystals of, (1) 1
flow in a capillary, (1) 1, 12, 29
force-temperature coefficient, (1) 127
friction of, (5) 1147
groove cracking resistance, (5) 1186

high temperature reinforcement, (3) 690
high temperature strength, (3) 69
injection molding of, (3) 620
load-deflection function for, (2) 440
low temperature flexibility of, (4) 1043
linear thermal expansion coefficient, (1) 127
internal energy of, (1) 127
mechanical properties of vulcanizates, (5) 1256
melting point as function of crystallizing temperature, (1) 1
melting point variation, (1) 1, 12, 29
Mooney-Rivlin constants of vulcanizates, (3) 707
Mooney-Rivlin plots of, (1) 127
nuclear magnetic resonance studies of, (5) 1273
oil diffusion coefficient—concentration function, (1) 87
oil migration in blend containing, (1) 87
quality for injection molding, (3) 620
Raman spectra of vulcanizates, (1) 71
reaction of tissue to, (2) 363
shear thinning of, (1) 1, 12, 29
spring rate of, (4) 1043
tensile strength retention of inner tubes of, (2) 397
strainwork of, (2) 440
thermodynamics, (1) 127
transmissibility, (2) 440
volume change on extension of vulcanizates of, (5) 1391
X-ray patterns of, (1) 1
Natural rubber vulcanization, (5) 1316
accelerator fragments in, (3) 771
continuous, (1) 294
crosslink distribution during, (3) 771
crosslink variation during, (3) 771
curatives for, (1) 881, 889, 898
injecting molding and, (3) 620
effect of equipment variables on, (3) 620
isomerism during, (1) 71; (4) 904
pendent accelerator group formation during, (3) 771
in swollen state, (3) 744
thiocarbamylamine disulfides in, (4) 881
thiocarbamyl amine sulfides in, (4) 881
thiazolyl morpholino disulfides in, (4) 898
Network, entanglements in, (5) 1256
interpenetrating, (3) 607
Network structure, concepts of, (5) 1208, 1227
effect of precure swelling on, (5) 1326
of EPDM vulcanizates, (5) 1334
Nickel dibutyldithiocarbamate, stabilizer for chlorosulfonated polyethylene, (5) 1410
Nitrile rubber, accelerators for blends with, (4) 1065
blends with EPDM, (4) 1065
blends with various rubbers, (3) 814
dielectric loss factor of, (1) 294
diffusion of sulfur in, (5) 1307
effect of mill size of mixing of, (2) 479
health hazard in manufacture of, (2) 512
hydroxy terminated, resin curing of, (4) 914
interpenetrating network from, (3) 609
resin curing of hydroxy terminated, (4) 914
Nitrogen adsorption, surface area measurement by, (2) 307; (5) 1287
Nitrosodimethylaniline, health hazard of, (2) 512
Norbornene, acceleration of radiation crosslinking by, (3) 587
Nuclear magnetic resonance spectroscopy, analysis of rubber by (5) 1273; 1278
carbon-13, (3) 871
of carbon black reinforced rubber, (5) 1273
carbon black-rubber interaction, (3) 843
of EPDM, (3) 781
microstructure by carbon-13, (3) 781
monomer sequence distribution by carbon-13, (3) 781
of natural rubber, (5) 1273
of rubbers from cycloolefins, (5) 1341
Nucleation of bubbles in rubbers, homogeneous, (5) 1363

O-rings, EPDM, (5) 1436
Oil, carbon-14 labelled, (1) 87
diffusion coefficient, equation, (1) 87
migration during dynamic aging, (1) 87
migration in rubbers, (1) 87
Oil extended rubber, abrasion studies of, (5) 1173
network structure of, (5) 1326
N-Oxydiethylene-2-benzothiazole sulfenamide, health hazard of, (2) 512
Oxygen, absorption by vulcanizates containing amine antioxidants, (4) 857
singlet, oxidations, (3) 642
Ozone resistance, use of EPDM for, (5) 1436

Particle size, carbon black, effect on glass transition temperature of black loaded rubber, (5) 1297
Pendent accelerator groups, (3) 771
Pentamethylene sulfide, Raman spectrum of, (1) 71
Perchloroethylene, health hazard of, (2) 512
Perfluororubber, dielectric properties, (3) 660
fluid resistance, (3) 660
heat resistance of, (3) 660
solvent resistance of, (3) 660
vulcanizate properties, (3) 660
Peroxide, dicumyl, cocuring agent with sulfur, (4) 923
cocuring with polyacrylates, (4) 923
crosslinking mechanism, (4) 923
vulcanization of polypropylene ether glycol rubbers, (4) 923
Phase angle, apparatus for measure of, (1) 249
effect of black loading on, (1) 258
effect of crosslink type on, (1) 258
effect of crosslink type on, (1) 258
effect of rubber on, (1) 258
effect of shear strain on, (1) 258
effect of temperature on, (1) 258

Phenolic antioxidants, (5) 1421
Phenolic resin, (4) 914
Phenyl-2-naphthylamine, antioxidant activity of, (4) 857
oxygen absorption of vulcanizates containing, (4) 857
Phenylene maleimide, cure activator for polyacrylate rubbers, (2) 344
Photooxidation of polymers, ABS polyblend, (3) 642
polybutadienes, (3) 642
Physical testing of rubber, interrelation between tests, (5) 1396
Pico abrader, abrasion studies, (5) 1173
Piperidinium pentamethylenedithiocarbamate, health hazard of, (2) 512
Piperidinosulfenyl chloride, (4) 881
Plastic modification, by EPDM, (4) 1130
Poisson's ratio, effect on sliding rubber, (3) 758
Polyacrylate rubbers, ammonium adipate cure of, (2) 344
compositions of, (2) 344
compounding of, (2) 344
crosslinking sites of, (2) 344
epoxide containing, (2) 344
mercaptoimidazoline, curative for, (2) 344
phenylene maleimide, cure activator for, (2) 344
self curing, (2) 344
stress relaxation of vulcanizates of, (2) 344
sulfur-soap cure of, (2) 344
tetramethylthiuram disulfide as curative for, (2) 344
thermal stability of vulcanizates, (2) 344
vulcanizates of, (2) 344
zinc diethyldithiocarbamate as curative for, (2) 344
Polybutadiene, abrasion studies of, (5) 1173
analysis of vulcanizates of, (5) 1278
bimodal molecular weight, (1) 166
blends with SBR, shift factor for carbon black equivalence in, (1) 199
blends with various rubbers, (3) 814
diffusion of oil in, (5) 1430
dynamic shear moduli of vulcanizates of, (1) 258
effect of carbon black loading on tensile stress relaxation of, (1) 185
effect on coefficient of wet friction of SBR blends, (5) 1443
effect on loss tangent maximum of molecular weight of, (1) 166
effect of temperature on dynamic modulus, (1) 166
effect of temperature on dynamic shear modulus, (1) 258
effect on temperature of loss tangent by crosslinking of, (1) 166
groove cracking resistance, (5) 1186
health hazard control in manufacture of, (2) 512
high temperature relaxation transitions, (1) 166
hydroperoxides of, (3) 642
hydroxyterminated, resin curing of, (4) 914
loss tangent and temperature, (1) 166
mechanical loss and temperature, (1) 166
oil diffusion coefficient-concentration function, (1) 87
oil migration in blends containing, (1) 87
oxidation by singlet oxygen, (3) 642
phase angle tangent of vulcanizates of, (1) 258
polyurethane chain extension of, (1) 152
Raman spectroscopic study of vulcanization of, (4) 904
Raman spectrum of, (4) 904
Raman spectra of vulcanizates, (1) 71; (4) 904
resin curing of, (4) 914
terpolymers with styrene-acrylonitrile, methyl styrene-acrylonitrile, and, styrene-acenaphthalene, (1) 62
Polychlorobutadiene, see Polychloroprene
Polychloroprene, blends with various rubbers, (3) 814
dielectric loss factor of, (1) 294
diffusion of sulfur in, (5) 1307
effect of mill size on mixing, (2) 479
health hazard in manufacture (2) 512
increased processing safety of, (5) 1449
interpenetrating network from, (3) 609
transmissibility of, (2) 440
vulcanization with tetramethylene thiourea, (5) 1449
Poly-2,3-dimethylbutadiene, terpolymers with styrene-acrylonitrile, methyl styrene-acrylonitrile, and styrene-acenaphthalene, (1) 62
Poly-p-dinitrosobenzene, health hazard of, (2) 512
Polyether, urethane based on, (1) 52
hydrolytic resistance of, (1) 52
Polyethylene, chemical stress relaxation of, (3) 579
radiation cured, (3) 579
Polyethylene terephthalate, tirecord, (3) 849
Polyisobutylene, relaxation of, (4) 1057
Polyisoprene, see also Natural rubber
analysis of vulcanizates of, (5) 1278
comparison with natural rubber, (5) 1432
crystallization of, (1) 1, 12, 29
diffusion of sulfur in, (5) 1307
effect of molecular structure on crystallization, (1) 12
effect of temperature on crystallization, (1) 12
friction of, (5) 1147
hazard control in manufacture, (2) 512
hydrogenated, as model of EPDM, (4) 1093
terpolymer with styrene-acrylonitrile, methyl styrene-acrylonitrile, and styrene-acenaphthalene, (1) 62
Polymer networks, structure of, (5) 1208, 1227, 1249
Polymerization, of cycloolefins, (5) 1341
ring opening, (5) 1341
Polyolefins, crosslinkable, (5) 1440

Polypropylene ether glycol rubbers, aging of vulcanizates, of, (4) 923
effect of black levels on, (4) 923
effect of diisocyanate concentration on, (4) 923
effect of peroxide-sulfur ratio of vulcanization, (4) 923
peroxide-acrylate cocuring of, (4) 923
peroxide crosslinking of, (4) 923
peroxide-sulfur cocuring of, (4) 923
vulcanizate properties of, (4) 923
Polystyrene, effect on loss and storage moduli of SBR, (3) 598
effect on glass transition temperature of SBR, (3) 598
reinforcement of SBR, (3) 598
Poly (trifluoropropyl) methyl siloxane, (5) 1350
Polyurethanes, aliphatic, (1) 52
chain end and plasticizer deviation from elastic theory, (1) 152
curing systems for, (4) 923
degradation in human body of, (2) 363
dependence of retractive force on chain ends, (1) 152
effect of temperature on properties, (1) 52
electrical properties, (1) 52
force-temperature coefficient, (1) 127
health hazard in manufacture of, (2) 512
hydrolytic stability of, (1) 52
interpenetrating network from, (3) 609
linear thermal expansion coefficient, (1) 127
liquid casting, (1) 52
loose chain ends in, (1) 152
Mooney-Rivlin plots, (1) 127
network theory, (1) 152
plasticizer-chain end equivalence, (1) 152
polybutadiene backbone in, (1) 152
polyether block copolymers, (5) 1447
from propropylene ether glycols, (4) 923
processing, (1) 52
reduction of stress decay by chain ends, (1) 152
strain and internal rotation, (1) 127
stress decay and crosslink density, (1) 152
tensile and tear strength, (1) 52
thermodynamics, (1) 127
thermoplastic, in bubble nucleation studies, (5) 1363
trifunctional crosslinks in, (1) 152
Porosity of carbon black, (5) 1287
Precure swelling, effect on network structure, (5) 1326
Prediction of hysteretic stresses in friction, (3) 758
Prooxidants, (5) 1421
Propylene inversion, in EPDM sequence distribution, (3) 771
Pyrometers, tire surface temperature measurement by, (2) 397

Quantimet data for carbon black particle measure, (1) 230

Radiation crosslinking, at cyclohexene sites, (3) 587
norbornenyl derivatives in, (3) 587
of polyethylene, (3) 579
Radicals, decomposition rate as a function of temperature, (3) 668
electron paramagnetic resonance spectra of, (3) 668
from mechanical degradation of vulcanizates, (3) 668
reaction with radical acceptors, (3) 668
relative stability of, (3) 668
structure and reactivity, (3) 668
traps for, (3) 668
di (t-butylphenol) disulfide as, (3) 668
di (isooctylphenol) disulfide as, (3) 668
di (trichlorophenyl) disulfide as, (3) 668
Radioactive sulfur, in diffusion measurements, (5) 1307
Radiotracers in diffusion studies, (5) 1430
Raman spectroscopy of rubber, (3) 854
vulcanization of polybutadiene and, (1) 71; (4) 904
of vulcanized rubbers, (1) 71; (4) 904
RAPRA translations, (4) G62; (5) G67
Refractive index of various rubbers, (3) 814
Reinforcement of rubber, mechanism of, (5) 1208, 1227, 1249
Reinforcement in rubber-polystyrene mode system, (3) 598
mechanically equivalent model for, (3) 598
vulcanization of, (3) 598
Reflectance of carbon blacks, surface area by, (5) 1287
Relaxation, mechanisms, (5) 1256
modulus, (4) 1057
Resin curing, adhesive quality, (4) 914
liquid rubbers, (4) 914
zinc oxide catalysis, (4) 914
Reversion in high temperature vulcanization, (5) 1316
Rheology of fibers, (3) 846
Rheometer, in vulcanization studies, (5) 1316
Rheometer, capillary, crystallization of rubber in, (1) 1, 12, 29
Ring opening polymerization, mechanism of, (5) 1341
Road surface, effect on tire wear and traction, (5) 1439
Rubber-carbon black interaction, (3) 843
nuclear magnetic resonance study of, (3) 843

Scanning electron microscopy, examination of abraded surfaces by, (5) 1451
Scintillation counting, (1) 87
Sealants, fluorosilicone, (5) 1350
Selenium diethyl (or dimethyl) dithiocarbamate, health hazard of, (2) 512
Segmental motion of rubber near carbon black particles, (5) 1297
Shape factor in filler reinforcement, (5) 1249
Shear, complex modulus, apparatus for measuring, (1) 249
effect of plasticizer on, (1) 258

effect of rubber on, (1) 258
effect of shear strain on, (1) 258
effect of temperature on, (1) 258
of SBR vulcanizates, (1) 258
Shear, dynamic modulus, effect of chemical promoters, (2) 440
effect of mill size on, (2) 479
effect of mixing on, (2) 479
effect on strainwork, (2) 440
effect of surface area of carbon black on, (2) 440
of fluorosilicone rubber, (2) 479
out-of-phase and in-phase, (2) 440
of silicone rubber, (2) 479
Shear, loss modulus, apparatus for measuring, (1) 249
effect of black loading on, (1) 258
effect of crosslinking, (1) 258
effect of plasticizer, (1) 258
effect of rubber, (1) 258
effect of strain on, (1) 258
effect of styrene content on SBR on, (1) 258
Shear modulus, and double strain amplitude of Butyl rubber, (2) 440
effect of carbon black surface area on, (2) 440
Shear, storage modulus, apparatus for measuring, (1) 249
effect of black loading on, (1) 258
effect of crosslinking on, (1) 258
effect of plasticizer on, (1) 258
effect of rubber on, (1) 258
effect of shear strain on, (1) 258
of SBR vulcanizates, (1) 258
effect of temperature on, (1) 258
Shear strain, effect of rubber on, (1) 258
Shear stress, activation energy, (1) 175
as function of strain, (1) 175
as function of temperature, (1) 175
relaxation, (1) 175
Shear thinning, (1) 12, 29
Shock absorbers, rubber tubes as, (5) 1380
Shoe soles, friction of various surfaces (5) 1434
Silanes, effect of organofunctionality on vulcanizate properties of EPDM, (4) 1080
effect on properties of peroxide cured EPDM, (4) 1080
effect on properties of sulfur cured EPDM, (4) 1080
Silane treated fillers, (5) 1437
Silica, dielectric loss factor, (1) 294
health hazard of, (2) 512
Silicone-carborane copolymer, stress relaxation of, (3) 579
Silicone rubber, application to surgery, (2) 363
chemical stress relaxation of, (3) 579
effect of mixing on, (2) 479
fluorosilicone, (5) 1350
implantation in human body of, (2) 263
interpenetrating network from, (3) 609
medical grade, (2) 263
properties of (2) 263
room temperature vulcanization of, (2) 363
vulcanization of, (2) 363
shear modulus of, (2) 479
Singlet oxygen oxidations, (3) 642
mechanism of, (3) 642
in solution, (3) 642
Skid, resistance, dry, blends of natural rubber and polybutadiene, (5) 1450
effect of road surface on, (5) 1439
Skid resistance, wet, blends of natural rubber and polybutadiene, (5) 1450
Sliding of rubber, (3) 758; (5) 1147
Soapstone, environmental control, (2) 512
Specific heat, EPDM rubbers, (4) 1093
Springs, rubber tubes as, (5) 1380
Spring rate, dynamic complex of SBR, (1) 258
effect of black loading on, (1) 258
effect of crosslinking on, (1) 258
Spring rate, dynamic elastic, for SBR, (1) 258
dynamic loss for SBR, (1) 258
Spring rates, effect of black loading on, (4) 1043
effect of black type on, (4) 1043
effect of EPDM grade on, (4) 1043
effect of processing oil on, (4) 1043
Spring rate, static, effect of black loading on, (1) 258
effect of crosslinking on, (1) 258
of SBR vulcanizates, (1) 258
Stabilization of polymers, mechanism of, (5) 1421
Stabilizers, for chlorosulfonated polyethylene, (5) 1410
Stannous octoate, catalyst for cure of polyurethanes, (1) 52
Starch in rubber, (3) 842
Statistical theory of rubber elasticity, (1) 127; (5) 1380
Stearic acid, effect on rubber crystallization, (1) 29
Stiffness, dynamic, (1) 258; (2) 440
static, (1) 258; (2) 440
Strain amplification factor, effect on Mooney-Rivlin constants for EPDM, (4) 1109
filled EPDM and, (4) 1109
Strain, effect on dynamic properties, (2) 440
Strain hardening of rubber vulcanizates, (5) 1208, 1227, 1249
Strain measurements in bias, bias belted, and radial tires, (5) 1453
Strainwork, effect of crosslink density on, (2) 440
effect of shear modulus, (2) 440
of natural rubber, (2) 440
Stress analysis, passenger tire sidewall, (5) 1452
Stress relaxation, of chlorosulfonated polyethylene vulcanizates, (5) 1410
continuous, (5) 1410
effect of composition of EPDM on, (4) 1057

effect on crosslink density on, (3) 579
of EPDM vulcanizates, (5) 1334
intermittent, (5) 1410
of natural rubber, (3) 707
effect of crosslink density on, (3) 707
of polymer networks, (5) 1256
Stress strain, behavior of swollen natural rubber, (3) 744
Mooney-Rivlin constants of, (3) 744
effect of pre-cure swelling on, (5) 1326
properties of rubber, (5) 1396
of rubber vulcanizates, (5) 1391
Structural characterization of vulcanizates, (3) 707, 771
network bound accelerator groups, (3) 771
Structure of fillers in reinforcement, (5) 1208, 1249
Styrene butadiene rubber, abrasion resistance of prestressed, (1) 214
abrasion studies of, (5) 1173
analysis of vulcanizates, (5) 1278
and blends, (3) 814; (4) 996
effect of glass transition temperature on wear, (4) 996
effect of microstructure on wear, (4) 996
effect of preparative methods on wear, (4) 996
effect of wear rate on skid, (4) 996
glass transitions of, (4) 996
wear-temperature function, (4) 996
wear of treads from, (4) 996
blends with EPDM, (4) 1065
effect of zinc dialkyldithiocarbamates on, (4) 1065
bonding to carbon black, (1) 175
damping coefficients of vulcanizates of, (1) 1258
determination of in blends, (5) 1429
dielectric loss factor, (1) 294
diffusion of oil in, (5) 1430
diffusion of sulfur in, (5) 1307
double strain amplitude and dynamic modulus, (2) 440
dynamic complex spring rate of vulcanizates, (1) 258
dynamic elastic spring rate of vulcanizates, (1) 258
dynamic loss spring rate of vulcanizates, (1) 258
dynamic shear modulii of vulcanizates, (1) 258
effect of black loading on stress relaxation of, (1) 185
effect of styrene content on glass transition temperature, (3) 598
effect of styrene content on wet friction, (5) 1443
filler reinforcement of, (5) 1208, 1227, 1249
first order rate of crosslink formation with accelerators, (4) 889
groove cracking resistance, (5) 1186
health hazard control in manufacture of, (2) 512
hydroxy terminated resin curing of, (4) 914
interpenetrating network from, (3) 609
loss modulus change with styrene content, (3) 598
oil diffusion coefficient—concentration function, (1) 87
oil migration in blends of, (1) 87
phase angle of, (1) 258
plasticizer effect on dynamic shear moduli of, (1) 258
reduced modulus of black loaded, (1) 199
reinforced with polystyrene, (3) 598
second order rate of crosslink formation with accelerators, (4) 889
shear stress relaxation of black loaded, (1) 175
shift factors for blacks in, (1) 199
static spring rate of vulcanizates of, (1) 258
storage modulus change with styrene content, (3) 598
terpolymer with styrene-acrylonitrile, methyl styrene-acrylonitrile, and styrene-acenaphthalene, (1) 62
thermal expansion of black filled, (5) 1297
transmissibility, (2) 440
Sulfenamide, see also Accelerators
in natural rubber, (4) 889
Sulfide, see also Accelerators
formation during vulcanization, (4) 904
Sulfur, cocuring agent with peroxide, (4) 923
diffusion in various rubbers, (5) 1307
Raman spectral study of vulcanization by, (1) 71; (4) 904
-soap, cure of polyacrylates by, (2) 344
vulcanization, kinetics of, (5) 1316
Surface area of carbon blacks, comparison of measurement methods, (5) 1287
Swelling of rubber vulcanizates, (5) 1208, 1227, 1249
effect of entanglement, (5) 1208, 1227, 1249
Swelling test for crosslink density, (5) 1316
Swollen rubber, vulcanization of, (3) 744
Swollen vulcanizates, stress strain of, (4) 1109; (5) 1391

Tack of rubbers, (5) 1432
Takayanagi model, (3) 598
Talc, environmental control, (2) 512
Tearing energy, EPDM, (5) 1203
measure of groove cracking, (5) 1203
Tellurium diethyldithiocarbamate, health hazard of, (2) 512
Tensile strength, adiabatic, (2) 397
effect of carbon black, surface area, (3) 728
surface activity, (3) 728
surface structure, (3) 728
effect of stress, (3) 728
effect of temperature, (3) 728
of glass yarn in rubber, (4) 937
effect of humidity, (4) 937
stress transfer, (4) 937
isothermal, (2) 397
Tensile stress patterns in sliding, (3) 758
effect of asperities, (3) 758
effect of Poisson's ratio, (3) 758
effect of surface friction, (3) 758

Terpolymers, glass transition temperatures of, (1) 62
law of corresponding states, (1) 62
mechanical properties, (1) 62
effect of matrix glass transition temperature, (1) 62
effect of molecular weight, (1) 62
Tetraethylthiuram disulfide, health hazard of, (2) 512
Tetrahydrothiophene, Raman spectrum of, (1) 71
Tetramethyldiaminodiphenylmethane, (4) 857
antioxidant activity of, (4) 857
oxygen absorption of vulcanizates containing, (4) 857
Tetramethyl-4-oxy piperidol, radical trap- (3) 668
Tetramethyl-p-phenylenediamine, antioxidant activity of, (4) 857
Tetramethylthiuram disulfide, cure of polyacrylate rubbers by, (2) 344
health hazard of, (2) 512
in Raman spectra of polybutadiene vulcanizates, (1) 71
Raman spectroscopic study of acceleration by, (4) 904
Tetramethylthiuram monosulfide, health hazard of, (2) 512
Thermal expansion of carbon black filled rubber in glassy state, (5) 1297
Thermal expansion of carbon black filled rubber in rubbery state, (5) 1297
Thermodynamics of rubbers, (1) 127
Thermoelastic behavior of EPDM, (4) 1093
effect of composition on, (4) 1093
Thermomechanical micromeasurement, (2) 479
at constant strain, (2) 479
at constant stress, (2) 479
9-Thiabicyclo (3.1.1)-2-nonene, (1) 71
Raman spectrum of, (1) 71
Thin layer chromatography of rubber chemicals, (2) 381
This bis (3-azabicyclo [3.2.2] nonene), (4) 881
Thiourea, tetramethyl, in vulcanization of polychloroprene, (5) 1449
Tires, aircraft, heat in, (2) 397
bias belted, sidewall strain analysis, (5) 1452
strain measurements, (5) 1453
bias ply, sidewall strain analysis, (5) 1452
strain measurements of, (5) 1453
wear of, (5) 1159
braking coefficient, variation with cornering coefficient, (4) 962
compounds for bus and truck, (3) 841
contour integral of, (1) 22
cord reinforcement of, (3) 848
cornering coefficient of, (4) 962
damping constant of, (2) 397
drag, effect of dynamic properties, (2) 397
dynamic properties of, (2) 397
dynamic spring constant, (2) 397
effect of conditions on wear, (1) 106
effect of rotation pattern on wear, (1) 106
effect of rolling resistance on temperature, (2) 397
effect of speed on contained air temperature, (2) 397
effect of speed and inflation pressure on resistance, (2) 397
effect of temperature on rolling resistance, (2) 397
effect of temperature on wear, (2) 397
friction of, factors in, (5) 1447
friction, heat of, (2) 397
groove cracking, (5) 1186, 1203
grooves, strain cycles in, (5) 1186
heat buildup and dynamic properties, (2) 440
heat dissipation of, (2) 397
heat in innerliners of, (2) 397
heat in innertubes of, (2) 397
mechanics, effect of traction and wear, (5) 1446
noise, reducing, (5) 1450
oil migration is simulated, (1) 87
power loss, (2) 397
radial ply, sidewall strain analysis of, (5) 1452
strain measurement of, (5) 1453
wear of, (5) 1159
rate of work of, (2) 397
sidewall, stress analysis of, (5) 1452
sidewall compounds containing EPDM, (5) 1436
steering properties of, (5) 1456
strain measurement in, (5) 1453
temperatures, (2) 397
calculation of, (2)397
and cornering force, (2) 397
danger zone of, (2) 397
distribution of, (2) 397
effect of inflation on, (2) 397
effect of operating conditions, (2) 397
effect on rolling resistance, (2) 397
effect of tire design, (2) 397
effect of tire materials, (2) 397
and flatspotting, (2) 397
liquid crystals and, (2) 397
ply separation and, (2) 397
pyrometer and, (2) 397
and running time, (2) 397
temperature sensitive crayons and, (2) 397
temperature sensitive paint and, (2) 397
thermocouples and, (2) 397
and tire failure, (2) 397
temperatures of contained air in, (2) 397
temperatures of sidewall surface of, (2) 397
temperatures of tread surface, of, (2) 397
test course for wear measurement, (1) 106
traveling waves in, (2) 397
traction, compounding effects on, (5) 1445, 1447
effect of carbon black type and loading, (5) 1445
effect of rubber type, (5) 1437

effect of road surface, (5) 1439, 1447
effect of tread pattern, (5) 1447
influence of tire mechanics, (5) 1446
wet cornering, (4) 962
tread designs for quiet tires, (5) 1450
truck, groove cracking, (5) 1186
wear, accelerated test for, (5) 1159
coefficient of friction, (5) 1159
effect of bias, belted bias, and radial constructions, (4) 952
effect of carbon black type, (5) 1445
effect of conditions, (1) 106
effect of environment, (4) 952
effect of rubber type, (5) 1437
effect of road surface, (5) 1159, 1439
effect of rotation pattern, (1) 106
effect of speed, (5) 1159
effect of test severity, (5) 1159
effect of water, (4) 952
effect of wheel position, (4) 952, 960
influence of tire mechanics, (5) 1446
measurement, (5) 1159
passenger, (5) 1159
road test, (5) 1173
studies of, (5) 1173
rates as a function of extent of wear, (4) 952
Tires, wet cornering forces, (4) 962
camber and, (4) 962
effect of road texture, (4) 962
effect of speed, (4) 962
effect of tread design, (4) 962
effect of tread hardness, (4) 962
effect of tread rubber, (4) 962
elastohydrodynamic lubrication, (4) 962
slip and, (4) 962
slip angle and, (4) 962
Tire belts, cords in radial, (3) 850
polyester for, (3) 850
Toluene diisocyanate, (1) 52
Transition metal ions, as antioxidants, (5) 1421
Transmissibility, mechanical of filled rubbers, (2) 440
variation with frequency, (2) 440
of various rubbers, (2) 440
Transmission rates of gases through plastic films, (2) 363
Trichloroethylene, health hazard of, (2) 512
Trichlorothiophenol, radical trap, (3) 668
Triethanolamine, effect on dielectric heating, (1) 294
Trimethylol propane, curing agents for urethanes, (1) 52
Tubes, theory of deformation between paralle plates, (5) 1380
Twist, effect of in polyethylene terephthalate tire cords, (3) 849

Vibrogrinding, of vulcanized rubbers, (3) 668
Vibromill, (2) 534
Vinyl silane, effect on properties of peroxide vulcanizates of EPDM, (4) 1080
Volume dilation, in extension of rubber vulcanizates, (5) 1391

Vulcanizate, analysis of rubber composition, (5) 1278
nuclear magnetic resonance studies of, (5) 1273
properties, effect of curatives, (3) 841
effect of zinc oxide, (3) 841
radical formation from mechanical degradation of, (3) 668
structure, (1) 71; (3) 711, 771
Raman spectral evidence for, (1) 71; (4) 904
vibrogrinding of, (3) 668
Vulcanization, of brominated ethylene propylene rubber, (3) 721
effect of zinc oxide, (3) 721
mechanism, (3) 721
effect of zinc oxide, (3) 721
mechanism, (3) 721
with mercaptobenzothiazole, (3) 721
with sulfur, (3) 721
cis trans isomerization during, (1) 71; (4) 904
compound formation during, (1) 71; (4) 904
continuous, (1) 294
review of, (3) 839
effect of carbon black on, (1) 199
effect of dynamic properties, (2) 440
effect of loss factor on continuous, (1) 294
of EPDM and its blends, (4) 1065
by dicumyl peroxide, (4) 1109
by halomethyl phenolic resins, (4) 914
at high temperatures, (5) 1316
formation of double bond conjugation during, (4) 904
hot air, (3) 838
by ionizing radiation, (3) 587
kinetics of (5) 1316
liquid curing medium for, (3) 838
of liquid rubbers, (3) 675
by peroxides, (3) 675
by thiols, (3) 675
of medical grade silicone rubber, (2) 363
microwave heating for, (1) 294
by peroxide-cocatalyst systems, (4) 923
radiation, (3) 838
Raman spectra of, (1) 71; (4) 904
rubber-polystyrene mode systems
sulfide formation during, (1) 71; (4) 904
of swollen rubber, (3) 744
systems for injection molding, (3) 620
system for liquid rubbers, (3) 754
Vulcanizing agents, aminothiocarbonyl amino disulfide as, (4) 881
3-azabicyclo (3.2.2)non-3-ylthiocarbonyl-morpholino disulfide as, (4) 881
3-azabicyclo (3.2.2)non-3-ylthiocarbonyl 3-azabicyclo (3.2.2)non-3-yl disulfide as, (4) 881
2-benzimidazolyl N-morpholino disulfide as, (4) 898
2-benzothiazolyl N-morpholino disulfide as, (4) 898
preparation of, (4) 898
vulcanizing character of, (4) 898

2-benzoxazolyl N-morpholino disulfide as, (4) 898
2-(5-chlorobenzothiazolyl) N-morpholino disulfide as, (4) 898
comparison of cure rates of, (4) 881, 898
diethylthiocarbamyl morpholino disulfide as, (4) 881
dimethylthiocarbamyl morpholino disulfide as, (4) 881
effect of substituents on curing character of, (4) 881, 898
2-(6-ethoxybenzothiazolyl) N-morpholino disulfide as, (4) 898
2-(4-methyl-5-acetylthiazolyl) N-morpholino disulfide as, (4) 898
2-(4-methyl-5-ethoxycarbonylthiazolyl) N-morpholino disulfide as, (4) 898
2-(4-methylthiazolyl) N-morpholino disulfide as, (4) 898
morpholinothiocarbonyl 3-azabicyclo (3.2.2)non-3-yl disulfide as, (4) 881
morpholinothiocarbonyl morpholino disulfide as, (4) 881
morpholinothiocarbonyl piperidino disulfide as, (4) 881
morpholinothiocarbonyl pyrrolidino disulfide as, (4) 881
piperidinothiocarbonyl piperidino disulfide as, (4) 881
2-(6-nitrobenzothiazolyl) N-morpholino disulfide as, (4) 898
piperidinothiocarbonyl morpholino as, (4) 881
pyrrolidinothiocarbonyl 3-azabicyclo (3.2.2)non-3-y disulfide as, (4) 881
Pyrrolidinothiocarbonyl morpholino disulfide as, (4) 881
scorch character of, (4) 881, 898
synthesis of various, (4) 881, 898

Wear, see Tires, wear of
Wet skid resistance of tires, (4) 969, 996
Williams, Landel, Ferry equation, application, (5) 1256
William abrader, studies with, (5) 1173
Windshield wiper blades, (5) 1440

Zinc dibutyldithiocarbamate, (4) 1065
Zinc diethyldithiocarbamate, curing agent for polyacrylate rubbers, (2) 344
health hazard of, (2) 512
Zinc dimethyldithiocarbamate, health hazard of, (2) 512
Zinc dodecylisopropyldithiocarbamate, (4) 1065
Zinc octadecylcyclohexyldithiocarbamate, (4) 1065
Zinc octadecylisopropyldithiocarbamate, (4) 1065
Zinc octylisopropyldithiocarbamate, (4) 1065
Zinc oxide, catalyst in resin curing, (4) 914